

Valspar® Masonry, Stucco & Brick Paint + Primer

No. 752600 Series

GENERAL DESCRIPTION

Valspar® Masonry, Stucco & Brick Paint + Primer is an Interior/Exterior coating that protects against chalking, alkali, and efflorescence. Plus, it gives a mold, mildew & algae-resistant coating. Ready in 2 hours, Rain-Ready Technology® guards the freshly painted surface from runs, blisters, or water marks once rain showers begin. This product may be applied to a surface with a pH of 6 to 10.

PRODUCT FEATURES

- Protects against chalking, alkali, and efflorescence
- Excellent hide, adhesion, and water repellence
- Provides a mold, mildew & algae-resistant coating
- Fade Resistant
- Dual Purpose (INT/EXT)
- 100% acrylic
- Lifetime Limited Warranty
- Can be applied over surfaces with a pH up to 10. If your pH is above 10 (hot stucco), use the Valspar® Masonry & Stucco Primer/Conditioner

RECOMMENDED USES

- Masonry
- Stucco
- Brick
- CMU
- Cement composition siding

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

Gallon – 4 per carton

5-gallon pail

Case Weight: 40 – 47 lbs.

COMPOSITION

Base and Fill Levels

	(oz/gal)
Ultra-White (752678, 752676)	126
Base 4 (752680, 752677)	116

APPLICATION

Paint only when paint, surface, and air temperatures are 50–90 °F (10–32 °C) during application and drying time. New masonry surfaces must be cured at least 30 days before painting. The pH must be 10 or lower. For pH higher than 10, refer to system recommendations. Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, premium-quality synthetic brush or airless sprayer. Always paint back into freshly painted areas and end up at a door, window, or outer edge. Clean up with warm, soapy water. No reduction necessary.

Airless Spray:

Pressure: 2000 PSI

Tip: 0.015–0.019"

Brush: premium-quality synthetic brush

Roller: premium-quality roller cover

SYSTEM

RECOMMENDATIONS

Previously Painted Surfaces:

Self-Priming

1-2 Coats: Valspar® Masonry, Stucco & Brick Paint

New Masonry Substrates (pH above 10-hot stucco):

1 Coat: Valspar® Masonry & Stucco

Primer/Conditioner

1-2 Coats: Valspar® Masonry, Stucco & Brick Paint

Certain deep or bright colors may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic

Pigment Type: Titanium Dioxide

Viscosity: 100-106 KU

Sheen: 0-5 units @ 60°

Flashpoint: N/A

VOC: < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

Volume Solids: 35.6%

Weight Solids: 50.0%

Weight Per Gallon: 11.03 Lb/gal

Practical Coverage: Covers approximately up to 400sq. ft. per gallon (37 m2 per 3.78 L) depending on surface porosity. No reduction necessary.

Recommended Film Thickness:

4.0 mil Wet 1.5 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

To The Touch: 1 hour

Recoat: 4 hours

Application Temperature: 50–90 °F (10–32 °C)

*Data reported is typical of Ultra White and will vary by color and batch.

CERTIFICATIONS

Current as of: 10/13/2022

MPI #	N/A
MPI GPS 1	N/A
MPI GPS 2	N/A
LEED (US)	Yes

REGULATORY COMPLIANCE

Current as of: 10/20/2022

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter.

Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state, and federal regulations.

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove all dirt, dust, chalk, rust, grease, wax, and mildew. Patch all cracks with appropriate patching compound. Remove any powdery dust and efflorescence and prime with this product. Efflorescence is caused by water entry within the wall itself. If efflorescence is present, find the source of water entry (cracked parapet cap tiles, open joints, or cracks, etc.) and repair before painting.

Concrete/Masonry/Stucco: Must be clean, dry, thoroughly cured and in good condition. Soft concrete or masonry surfaces should be primed with this product.

Concrete Block/Cinder Block: Fill the pores of bare concrete block with a latex block filler, then topcoat. Do not use block filler as the sole exterior finish. Block filler must always be top coated on exterior uses.

Previously Painted Surfaces: Power wash or scrape off loose and peeling paint. Then spot prime peeled areas with this product. Thoroughly remove surface chalk by vigorous washing and rinse surface well.

Clean Mildew from the Surface:

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1-part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

MANUFACTURER'S LIFETIME LIMITED WARRANTY

If this product, when applied according to product application instructions, to a properly prepared exterior residential surface, peels or blisters, for as long as you own your residence, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product sufficient to repair the peeling or blistering free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the product. This is your sole remedy under this warranty. This warranty is made to the original residential consumer paint purchaser and is not transferable. **THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which vary from state to state. Valsparpaint.com/1-877-VALSPAR.

CAUTIONS

Contains Crystalline Silica. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.

Cleveland, OH 44115
888.313.5569
valsparpaint.com
Revised: 10/20/22
VALMSB