



# Valspar® Cabinet and Furniture Semi-Gloss Paint

## No. 740159 Series

### GENERAL DESCRIPTION

Valspar Cabinet and Furniture Paint dries to a smooth factory-like finish and stands up to daily use leaving a fade-, scratch-, and scuff resistant finish. Most projects will require little-to-no prep work. The oil-enriched formula provides exceptional durability with no brush marks.

### PRODUCT FEATURES

- Oil enriched enamel
- Strong, factory-like finish
- Fade-, scratch- & scuff- resistant
- No sanding or priming needed
- Soap-and-water cleanup
- Tintable to 1000+ colors

### RECOMMENDED USES

Bare wood, previously painted wood or metal in sound condition, and properly prepared laminate.

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material. Protect from freezing.

**Packaging:**

- Quart – 4 per carton
- Gallon – 4 per carton

### COMPOSITION

**Base and Fill Levels**

(oz./gal.)

**Ultra White / Tint Base 1** 124  
(740158, 740159)

**Base 4** 116  
(740162, 740163)

### APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller or polyester brush. Note:

Two thin coats are required. Bare wood and some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage. Allow to dry thoroughly before recoating or use.

**Airless Spray:**

- Pressure: 2000 PSI
- Tip: 0.015–0.019"

**Brush:** premium-quality synthetic

**Roller:** 3/6" – 3/8" premium-quality

DO NOT USE FOAM ROLLER

### SYSTEM

### RECOMMENDATIONS

**New Wood:**

2 Coats: Valspar® Cabinet and Furniture Paint

**Previously Paint Surfaces:**

2 Coats: Valspar® Cabinet and Furniture Paint

**Laminate:**

1 Coat: Valspar® Bonding Primer

2 Coats: Valspar® Cabinet and Furniture Paint

For improved adhesion on extremely smooth surfaces use 1 coat of Valspar® Bonding Primer

Recommended one coat of primer if the painting project requires a bold transition. This will improve the topcoat hiding power.

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic-Alkyd Hybrid

**Viscosity:** 87–95 Krebs Units

**Sheen:** 45-55 @ 60°

**Flashpoint:** N/A

**VOC (g/L):** < 50 g/L □ 0.42 lb./gal as per 40 CFR 59.406

**Weight Per Gallon:** 11 lbs.

**Volume Solids:** 35%

**Weight Solids:** 51%

**Practical Coverage:** Covers approximately 400 sq. ft. per gallon (37 m<sup>2</sup> per 3.78 L) depending on surface porosity.

**Recommended Film Thickness:**

4.0 mil Wet      1.4 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To Touch:** 4 hours

**Recoat:** 8-12 hours

**Washing Instructions:** Wait at least 7 days before washing with a mild detergent and soft sponge

**Application Temperature:** 50–90 °F (10–32 °C)

\*Data reported is typical of White and will vary by color and batch.

### REGULATORY COMPLIANCE

Current as of: 3/18/2020

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

### CLEANUP AND DISPOSAL

Clean up with warm, soapy water. If product has fully dried, you may need mineral spirits. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.



# Valspar® Cabinet and Furniture Semi-Gloss Paint

## No. 740159 Series

### **SURFACE PREPARATION**

#### **General:**

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Remove gloss from shiny surfaces. Patch cracks and spot prime prior to painting. For best results on heavily stained areas, apply one coat of an appropriate interior latex primer.

#### **Wood:**

Sand wood smooth and patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Int/Ext Bonding Primer before applying the finish coat(s).

#### **Metal:**

Remove all oil, grease, dirt and oxidation from surface. All bare metal surfaces should be primed with Valspar® DTM Acrylic Primer or Valspar® Anti-Rust Primer.

### **LEAD WARNING**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **LIFETIME LIMITED WARRANTY**

If this product, when applied according to product application instructions to a properly prepared interior surface, fails to perform to your complete satisfaction for as long as you own your home, Valspar shall, upon presentation of proof of purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the product. This is your sole remedy under this warranty. This warranty is made to the original residential consumer paint purchaser and is not transferable. This warranty excludes (1) labor or costs associated with labor for the application or removal of any product, and (2) any indirect, special, incidental or consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. [Valsparpaint.com/1-877-VALSPAR](http://Valsparpaint.com/1-877-VALSPAR).

### **CAUTIONS**

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

Valspar, Cleveland, Ohio 44115  
Revised: 3/18/20