



# Valspar® Ultra® Interior Latex Satin Paint

## No. 935297 Series

### GENERAL DESCRIPTION

Ultra® Stain Resistant Paint + Primer delivers an everyday washable™, smooth finish with good stain resistance. The 100% acrylic formula provides protection from everyday scuffs, marks & wear making it easy to wash off. This Valspar® product is a great choice for customers needing a paint that works everyday and resists scrubs and stains. Ideal for properly prepared interior walls, and ceilings, previously painted or bare drywall, plaster, masonry and primed metal.

### PRODUCT FEATURES

- Everyday washable.™ Everyday stains wash off with ease
- Provides everyday protection against scuffs, marks and wear
- Smooth, washable finish
- Built-in primer gives better coverage in less time
- 100% acrylic latex
- Mold- and mildew-resistant finish
- Greenguard Gold certified for ultra-low emissions
- Backed by our Lifetime Warranty

### RECOMMENDED USES

Properly prepared interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement and metal.

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material.

Protect from freezing.

**Packaging:**

- Quart – 4 per carton
- Gallon – 4 per carton
- 5 Gallon pail

### COMPOSITION

|                                      | Base and Fill Levels (oz./gal.) |
|--------------------------------------|---------------------------------|
| Tint Base A (935285, 935297, 935307) | 124                             |
| Tint Base B (935283, 935295, 935305) | 120                             |
| Tint Base C (935284, 935296)         | 116                             |

### APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, polyester brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction. Note: Some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage.

**Airless Spray:**

- Pressure: 2000 PSI
- Tip: 0.015–0.021"

**Brush:** Premium-quality polyester

**Roller:** Premium-quality roller 3/8" nap

### SYSTEM

#### RECOMMENDATIONS

**Plaster:**

Prime with Ultra Interior Latex Satin Paint

1–2 Coats: Ultra Interior Latex Satin Paint

**New Wood:**

Prime with Ultra Interior Latex Satin Paint

1–2 Coats: Ultra Interior Latex Satin Paint

**New Drywall:**

Prime with Ultra Interior Latex Satin Paint

1–2 Coats: Ultra Interior Latex Satin Paint

**Brick:**

Prime with Ultra Interior Latex Satin Paint

1–2 Coats: Ultra Interior Latex Satin Paint

**Cement:**

Prime with Ultra Interior Latex Satin Paint

1–2 Coats: Ultra Interior Latex Satin Paint

**Previously Painted Surfaces:**

Prime with Ultra Interior Latex Satin Paint

1–2 Coats: Ultra Interior Latex Satin Paint

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic

**Pigment Type:** Titanium Dioxide

**Viscosity:** 95–101 Krebs Units

**Gloss:** 20–30 Units @ 60° angle

**Flashpoint:** N/A

**VOC (g/L):** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

**Volume Solids:** 39%

**Weight Solids:** 52%

**Weight Per Gallon:** 10.54 lbs./gal.

**Practical Coverage:** 400 sq. ft. per gallon (37 m<sup>2</sup> per 3.78 L) depending on surface porosity. Do not thin

**Recommended Film Thickness:**

4.0 mil Wet      1.6 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To The Touch:** 30–60 minutes

**Recoat:** 2–4 hours

**Washing:** Allow at least 7 days before washing.

Use mild detergent and sponge.

**Application Temperature:** 50–90 °F (10–32 °C)

### CERTIFICATIONS

MPI # 146 - Pending

LEED (US) Yes

LEED (Canada) Yes

LEED (US) Yes

LEED (Canada) Yes

UL GREENGUARD Gold Approved

### REGULATORY COMPLIANCE

Current as of: 1/5/2018

SCAQMD Yes

CARB 2000 SCM Yes

CARB 2007 SCM Yes

OTC/LADCO Yes

US National Yes

### CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.



# Valspar Ultra® Interior Latex Satin Paint

## No. 935297 Series

### SURFACE PREPARATION

#### **General:**

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Remove gloss from shiny surfaces. Patch cracks and spot prime. This paint can be used to prime patched areas and bare surfaces before applying the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, prime with an appropriate tintable primer for optimal color accuracy and coverage.

#### **Drywall and Plaster:**

Fill cracks, pits and voids with patching compound. Allow new plaster to fully cure and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar Ultra®.

#### **Wood:**

Sand wood smooth and patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar Ultra®.

#### **Metal:**

Prime bare metal surfaces with Valspar® Anti-Rust Primer.

### LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### MANUFACTURER'S LIFETIME LIMITED WARRANTY

This product is warranted for your complete satisfaction for as long as you reside in your home. This warranty covers product that is applied to a properly prepared residential surface in accordance with label directions and excludes product failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

### CAUTIONS

WARNING! Contains Crystalline Silica. KEEP OUT OF THE REACH OF CHILDREN. May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. DO NOT TAKE INTERNALLY. Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

UCL 4.1s

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:**  
**1-888-345-5732**

Valspar  
Cleveland, OH  
[valsparpaint.com](http://valsparpaint.com)  
888.313.5569  
Revised: 7/29/2019  
VALULTINTSAT