



Valspar® SeasonPLUS™ Exterior 100% Acrylic Satin Paint + Primer

No. 636337-39, 636347-48, 636352-54 Series

GENERAL DESCRIPTION

Valspar® SeasonPLUS™ Fade-Resistant Paint + Primer with complete color defense™ blocks UV rays plus gives a mold- and mildew-resistant finish for a longer lasting color. This 100% acrylic formula also offers excellent hide along with a strong finish that resists cracking and peeling.

PRODUCT FEATURES

- Complete color defense™
- Fade-Resistant Paint + Primer
- Excellent hide and coverage
- Extra protection from cracking, peeling and blistering
- Provides a mold- and mildew-resistant coating
- Low-temp application
- 100% acrylic
- Lifetime warranty

RECOMMENDED USES

Properly prepared exterior surfaces of wood, hardboard, aluminum siding, vinyl siding, masonry, brick, stucco, cement composition panels and metal. Not for use on floors.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

- Quart – 4 per carton
- Gallon – 4 per carton
- 5 gallon pail

COMPOSITION

Base and Fill Levels

	(oz./gal.)
Extra White (636352, 636353, 636354)	124
Deep (636337, 636338, 636339)	118
Ultra Deep (636347, 636348)	116

APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. When air temperature is 35°F, substrates may be colder; prior to painting, check to be sure the air, surface, and material temperatures are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 2-3 hours. Do not apply when air or surface temperatures may drop below 35°F within 48 hours. On large expanses of metal siding, the air, surface, and material temperatures must be 50°F or higher. These recommendations are a starting point only. Due to variability in sprayers, we recommend testing your spray pattern and flow before proceeding. Always paint back into freshly painted areas and end up at a door, window or outer edge. Move windows after 1 hour to prevent sticking.

Airless Spray:

Pressure: 2000 PSI
Tip: 0.015–0.019"

Brush: premium-quality nylon/polyester brush

Roller: premium-quality 3/8–3/4" nap synthetic cover

SYSTEM RECOMMENDATIONS

Aluminum & Aluminum Siding¹, Siding¹, Galvanized Steel¹, Steel, Vinyl Siding

2 cts. SeasonPLUS™ Exterior Paint + Primer
Brick, Concrete Block, CMU

1 ct. Of an appropriate primer or filler

2 cts. SeasonPLUS™ Exterior Paint + Primer
Cement Composition Siding/Panels

1 ct. Of an appropriate primer

2 cts. SeasonPLUS™ Exterior Paint + Primer
Stucco, Cement, Concrete

1 ct. Of an appropriate primer

2 cts. SeasonPLUS™ Exterior Paint + Primer
Wood, Plywood/Composition Board

1 ct. Of an appropriate primer

2 cts. SeasonPLUS™ Exterior Paint + Primer
Wood (Cedar, Redwood)³

1 ct. Of an appropriate stain-blocking primer

2 cts. SeasonPLUS™ Exterior Paint + Primer

- 1 On large expanses of metal siding, the air, surface, and material temperatures must be 50°F or higher.
- 2 Not for use at temperatures under 50°F. See specific primer label for that product's application conditions.
- 3 Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. For best results on these woods, use a coat of stain-blocking primer.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic

Pigment Type: Titanium dioxide

Viscosity: Kinematic (40°C (104°F)): >0.205 cm²/s (>20.5 cSt)

Gloss: 10-20 Units 60° angle

Flashpoint: N/A

VOC (g/L): less than 50 g/L 0.42 lb/gal as per 40 CFR 59.406

Volume Solids: 37.70 ± 2%

Weight Solids: 49.33 ± 2%

Weight Per Gallon: 10.22 lbs./gal.

Practical Coverage: Covers approximately 250–400 sq. ft. per gallon (23–37 m² per 3.78 L) depending on surface porosity. Do not thin.

Recommended Film Thickness:

6.4–4 mil wet 2.5–1.6 mil dry

Dry Time @ 77 °F and 50% Relative Humidity

@ 35-45 °F @ 45-90 °F

Touch: 2 hour 1 hour

Recoat: 24-48 hours 4 hours

Drying and recoat times are temperature, humidity, and film thickness dependent.

Application Temperature: 35–90 °F (1–32 °C)

CERTIFICATIONS

Current as of: 1/2/2018

MPI #	11
MPI GPS 1	Yes
MPI GPS 2	Yes
LEED (US)	Yes
LEED (Canada)	Yes

REGULATORY COMPLIANCE

Current as of: 1/2/2018

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.



Valspar® SeasonPLUS™ Exterior 100% Acrylic Satin Paint + Primer

No. 636337-39, 636347-48, 636352-54 Series

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or damaged paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Caulk around windows, doors, and other openings after spot priming bare surfaces with SeasonPLUS™ Exterior Paint + Primer.

Aluminum and Galvanized Steel

Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, steel wool or other abrading method.

Cement Composition Siding/Panels

Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 8, prime with an appropriate primer.

Wood, Plywood, Composition Board

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed.

Masonry, Concrete, Cement, Block

All new surfaces must be cured according to the supplier's recommendations – usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with an appropriate masonry primer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant. For extremely porous surfaces, a coat of block filler may be required to achieve a pinhole free film.

SURFACE PREPARATION

Steel

Rust and mill scale must be removed using sandpaper, steel wool, or other abrading method. Bare steel must be primed the same day as cleaned.

Stucco

Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 5-7 days and prime with masonry primer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.

Vinyl

Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly. Repaint vinyl siding with a color similar to the original color to avoid excess heat absorption to prevent buckling or warping.

Caulking

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.

Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

LIFETIME LIMITED WARRANTY

This product is warranted for your complete satisfaction for as long as you reside in your home. This warranty covers product that is applied to a properly prepared residential surface in accordance with label directions and excludes product failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

CAUTIONS

For exterior use only. Protect from freezing.

LABEL CAUTIONS

CAUTIONS CONTAINS ZINC. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732

Valspar, Cleveland, OH 44115
888.313.5569
valsparpaint.com
Revised: 1/2/18