

valsparPRO™ ValsparPRO® Express Coat™ Interior Latex Flat Paint

No. 935355 Series

GENERAL DESCRIPTION

Express Coat™ delivers a good product that is affordable. The acrylic formula provides good hide and coverage while applying easily by brush, roll, and spray. This **ValsparPRO®** product is the right choice for customers doing maintenance work where touch up and quick work is necessary. Ideal for properly prepared interior walls, and ceilings, previously painted or bare drywall, plaster, masonry and primed metal.

PRODUCT FEATURES

- Brush, roller and spray application
- Fast dry and recoat time
- Soap and water cleanup

RECOMMENDED USES

Properly prepared interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement and metal.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material.

Protect from freezing.

Packaging:

- Gallon – 4 per carton
- 5 Gallon pail

COMPOSITION

	Base and Fill Levels (oz./gal.)
Antique White (935355, 935357)	128
Extra White (935348, 935351)	124
Tint Base C (935346)	116

APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, premium-quality synthetic brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction. Note: Some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage.

Airless Spray:

- Pressure: 2000 PSI
- Tip: 0.015–0.021"

Brush: Premium-quality synthetic

Roller: Premium-quality roller 3/8" nap

SYSTEM

RECOMMENDATIONS

Drywall/Wallboard (new):

- 1 Coat: Valspar® Primer
- 1–2 Coats: Express Coat Interior Latex Flat Paint

Plaster:

- 1 Coat: Valspar® Primer
- 1–2 Coats: Express Coat Interior Latex Flat Paint

New Wood/Composition Board:

- 1 Coat: Valspar® Int/Ext Bonding Primer
- 1–2 Coats: Express Coat Interior Latex Flat Paint

Interior Concrete Block:

- 1 Coat: Valspar® Block filler
- 1–2 Coats: Express Coat Interior Latex Flat Paint

Masonry:

- 1 Coat: Valspar® Masonry and Stucco Primer
- 1–2 Coats: Express Coat Interior Latex Flat Paint

Previously Painted Surfaces:

- 1–2 Coats: Express Coat Interior Latex Flat Paint

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic

Pigment Type: Titanium Dioxide

Viscosity: 103–109 Krebs Units

Gloss: 0–5 Units @ 85° angle

Flashpoint: N/A

VOC (g/L): < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

Volume Solids: 26%

Weight Solids: 43%

Weight Per Gallon: 10.92 lbs./gal.

Practical Coverage: 400 sq. ft. per gallon (37 m² per 3.78 L) depending on surface porosity. Do not thin

Recommended Film Thickness:

- 4.0 mil Wet 1.5 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity To The Touch: 30–60 minutes

Recoat: 2–4 hours

Washing: Allow at least 7 days before washing.

Use mild detergent and sponge.

Application Temperature: 50–90 °F (10–32 °C)

CERTIFICATIONS

- LEED (US) Yes
- LEED (Canada) Yes

REGULATORY COMPLIANCE

Current as of: 6/11/2018

- SCAQMD Yes
- CARB 2000 SCM Yes
- CARB 2007 SCM Yes
- OTC/LADCO Yes
- US National Yes

CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Remove gloss from shiny surfaces. Patch cracks and spot prime. This paint can be used to prime patched areas and bare surfaces before applying the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, prime with an appropriate tintable primer for optimal color accuracy and coverage.

Drywall and Plaster:

Fill cracks, pits and voids with patching compound. Allow new plaster to fully cure and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Zero VOC Primer.

Wood:

Sand wood smooth. Patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Interior/Exterior Bonding Primer.

Concrete Block:

Concrete block surfaces and mortar should be fully cured, usually 30 days. Remove all loose material or dust. Fill pores of bare concrete block with Valspar® Block filler, then top coat.

Masonry:

New concrete, masonry surfaces and mortar should be cured, usually 30 days. Remove all form release or curing agents. Remove all loose material or dust. Prime bare surfaces with Valspar® Masonry and Stucco Primer, then top coat.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

MANUFACTURER'S LIFETIME LIMITED WARRANTY

This product is warranted for your complete satisfaction for as long as you reside in your home. This warranty covers product that is applied to a properly prepared residential surface in accordance with label directions and excludes product failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

CAUTIONS

Contains Crystalline Silica. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

16 (01/10)

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

Valspar
Cleveland, OH
valsparpaint.com
888.313.5569

VALPROEXPRSTINTFLT