

### GENERAL DESCRIPTION

Valspar® 4000™ Zero VOC Interior Latex is commercial grade paint with good hide & coverage and great touch-up. It creates a durable film with a smooth, uniform finish that hides imperfections. Ideal for commercial environments, residential re-paint and new home construction; this paint is formulated for spray, brush and roll application on properly prepared interior walls and ceilings.

### PRODUCT FEATURES

- Zero VOC
- Good hide & coverage
- Great touch-up and fast recoat time
- Easy application spray, brush and roll
- Smooth, uniform finish
- Soap and water cleanup



### RECOMMENDED USES

Properly prepared interior walls and ceilings including:

- Previously painted surfaces
- Drywall
- Plaster
- Wood
- Masonry
- Metal

### PART NUMBER DETAILS

White Base:

9447508	GAL	124 oz
9447510	5 GAL	620 oz

High Hide White:

9447509	GAL	128 oz
9447511	5 GAL	640 oz

Base C:

9460040	GAL	116 oz
---------	-----	--------

### APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium quality roller, premium-quality synthetic brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction. Note: Some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage.

#### Airless Spray:

Pressure: 2000 psi  
Tip: 0.15" - .021"

**Brush:** Premium-quality synthetic

**Roller:** Premium-quality roller 3/8" nap

**Thinning:** Thin with up to 8 oz. water per gallon only if paint is too thick for sprayer.

### SYSTEM RECOMMENDATIONS

Previously Painted Surfaces:

2 Coats: Valspar® 4000™ Zero VOC Flat

Drywall:

1 Coat: Valspar® Multi-Surface Primer/Sealer  
2 Coats: Valspar® 4000™ Zero VOC Flat

Plaster:

1 Coat: Valspar® Multi-Surface Primer/Sealer  
2 Coats: Valspar® 4000™ Zero VOC Flat

Wood:

1 Coat: Valspar® Multi-Surface Primer/Sealer  
2 Coats: Valspar® 4000™ Zero VOC Flat

Masonry:

1 Coat: Appropriate Masonry Primer/Conditioner  
2 Coats: Valspar® 4000™ Zero VOC Flat

Metal:

1 Coat: Valspar® DTM (Direct to Metal) Primer  
2 Coats: Valspar® 4000™ Zero VOC Flat

Recommended Valspar® High-Hiding Primer/Sealer if the painting project requires a bold color transition.

### PRODUCT SPECIFICATIONS\*

**Vehicle Type:** Vinyl Acrylic

**VOC (g/L):** < 50 g/L  
0.42 lbs./gal as per 40 CFR 59.406

**Flashpoint:** N/A

**Viscosity:** 97 – 107 Krebs Units

**Volume Solids:** 38%

**Weight Solids:** 57%

**Weight Per Gallon:** 12.0 lbs./gal.

**Sheen:** 0 – 5 Units @ 85°

**Coverage:** Approximately 350–450 sq. ft. per gallon (32–42 m2 per 3.78 L). Less on rough or porous surfaces.

**Recommended Film Thickness:**

4.0 mils Wet  
1.5 mils Dry

**Dry Time:** @77°F, 50% Relative Humidity

**To The Touch:** 1 hour  
**Recoat:** 4 hours

**Application Temperature:**

50–90 °F  
10–32 °C

\*Product specifications based on White Base

### REGULATORY COMPLIANCE

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

### **SURFACE PREPARATION**

**General:** Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Remove gloss from shiny surfaces. Patch cracks and spot prime. Valspar Signature® paint can be used to prime patched areas and bare surfaces before applying the finish coat. For best results on heavily stained areas, drastic color changes or deep, vivid colors, prime with Valspar® Interior Multi-Purpose Primer/Sealer for optimal color accuracy and coverage.

**Clean mildew from the surface:** Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1-part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

**Drywall and Plaster:** Fill cracks, pits and voids with patching compound. Allow new plaster to fully cure and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar Multi-Surface Primer/Sealer.

**Wood:** Sand wood smooth and patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar Multi-Surface Primer/Sealer.

**Masonry:** New concrete, masonry surfaces and mortar should be cured, usually 30 days. Remove all form release or curing agents. Remove all loose material or dust. Spot prime soft concrete or masonry surfaces with appropriate masonry conditioner.

**Metal:** Prime bare metal surfaces with Valspar® Anti-Rust Primer.

### **LEAD WARNING**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **LIMITED WARRANTY**

This product is warranted for your complete satisfaction for as long as you reside in your home. This warranty covers product that is applied to a properly prepared residential surface in accordance with label directions and excludes product failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

### **CAUTIONS**

**CONTAINS CRYSTALLINE SILICA.** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure.

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

Valspar  
Cleveland, OH [valsparpaint.com](http://valsparpaint.com)  
888.313.5569  
VAL4000INTFLT