



4000 Ceiling Paint

CHARACTERISTICS

Valspar® 4000™ Ceiling Paint is a commercial grade ceiling paint with good hide & coverage. Formulated specifically for application to ceilings, 4000 Ceiling Paint's high hiding pigments dry quickly to a matte finish that reduces reflection and glare in all lighting conditions. 4000 Ceiling Paint applies easily, with minimal spattering, providing a smooth, uniform finish.

- Zero VOC
- Good Hide & Coverage
- Great Touch-Up and Fast Recoat Time
- Easy to Apply – Spray, Brush or Roll

Coverage: Up to 400 sq ft/gal depending on surface texture and porosity.

Drying Time, @77°F, 50% RH:

Touch: 2 hours

Recoat: 4 hours

*Drying and recoat times are temperature, humidity, and film thickness dependent

Finish: 0-9 units @ 85°

Flash Point: N/A

Vehicle Type: Vinyl Acetate
Ethylene Copolymer

VOC (less exempt solvents):

< 50 g/L;

As per 40 CFR 59.406

Volume Solids: 25 ± 2%

Weight Solids: 42 ± 2%

Weight per Gallon: 10.8 lbs/gal

Base and Fill Levels (fl. oz./gal.):

White 128

WHERE TO USE

Properly prepared durable textured or plain interior ceilings including previously painted and primed plaster, drywall, acoustical tile and wood.

SHIPPING & PACKAGING

Freight Classification:

Paint or paint related material. Protect from freezing.

Packaging:

9497911 1 Gallon – 4 per carton

9497912 5 Gallon – Each

APPLICATION

Stir paint thoroughly before and during use. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, roller or airless sprayer. Thinning not required. Certain deep or bright colors may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

For additional application tips, go to valspar.com.

Brush

Use a premium-quality nylon or polyester brush.

Roller

Use a premium-quality synthetic, 3/8 – 1/2" nap roller.

Spray—Airless

Pressure: 2000 psi

Tip: .015"-.021"

CLEANUP/DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

SURFACE PREPARATION

General:

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Patch cracks and spot prime. Remove gloss from shiny surfaces.

Acoustical Tile:

Vacuum or dust tiles to remove embedded dust. To maintain the sound absorbing qualities of the tile, do not use a primer. Apply ceiling paint directly to the tiles. Test vinyl-coated tiles to ensure adhesion. Do not attempt to fill or clog acoustical perforations.

“Blown-on” Soft-Fibered Ceilings:

Caution! All water-based paints will loosen or deteriorate a “blown-on” soft-fibered ceiling surface and make for a difficult repair. If you are not sure about your ceiling texture type, apply a small test area in a closet or other hidden spot. If deterioration occurs and if painting is necessary, priming with an oil-based primer may help minimize the deterioration. Do not use a latex primer.

Clean Mildew from the Surface:

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.



4000 Ceiling Paint

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARRANTY

LIMITED WARRANTY This product is warranted to meet the application, appearance, and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal or lesser value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state. **CONTRACTOR AND COMMERCIAL CUSTOMERS:** When used for commercial or nonresidential applications, this product is warranted to perform as indicated on the product label and to be free of material defects. At its option, Valspar will replace or refund the original purchase price of this product if it does not perform as labeled or is proven to be defective. All other warranty terms above apply. Valsparpaint.com /1-877-VALSPAR.

CAUTIONS

CONTAINS CRYSTALLINE SILICA.

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use.

Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

Cleveland, OH
valsparpaint.com
877-825-7727
Revised: 02/28/2024