

# valsparPRO™ Valspar® 4000 Int/Ext Alkyd Semi-Gloss

---

## No. 9451858 Series

### GENERAL DESCRIPTION

A high quality, alkyd enamel designed for interior and exterior use. The silky smooth formula glides on easily and clings to edges and corners without sagging. Formulated for the professional; it can be brushed, sprayed and rolled.

### PRODUCT FEATURES

- Excellent durability
- Excellent flow and leveling
- Long lasting uniform finish
- Easy one coat application
- Interior and exterior use

### RECOMMENDED USES

Properly prepared interior:

- Wood
- Metal
- Trim, cabinets and accents
- Properly prepared plaster and drywall
- Ferrous metal
- Concrete and masonry
- Do Not use on glazed brick, decks, floors or steps

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material.

**Packaging:**

Gallon – 2 per carton

**Case Weight:** 23 lbs.

### COMPOSITION

**Base and Fill Levels**  
(oz./gal.)

White (9451858)	128
Pastel Base (9451859)	126

### APPLICATORS

Stir thoroughly and intermix multiple containers. Apply only when paint, surface and air temperatures are 50–90 °F (10–32 °C) during application and drying time. Apply with a premium-quality roller, premium-quality synthetic brush or airless sprayer. The recommendations below are a starting point only. Due to variability in sprayers, we recommend testing your spray pattern and flow before proceeding.

**Airless Spray:**

Pressure: 2000 PSI

Tip: 0.015–0.021"

**Brush:** premium-quality synthetic

**Roller:** Premium-quality roller 1/4–3/4" nap

### SYSTEM

#### RECOMMENDATIONS

**Drywall/Wallboard (new):**

1 Coat: Valspar® Interior Drywall Primer-Sealer

1–2 Coats: Contractor Coat Int/Ext Alkyd Gloss

**Plaster:**

1 Coat: Valspar® Interior Primer-Sealer

1–2 Coats: Contractor Coat Int/Ext Alkyd Gloss

**Interior Wood:**

1 Coat: Valspar® Interior Wood Primer or

Valspar® Interior Drywall Primer

1–2 Coats: Contractor Coat Int/Ext Alkyd Gloss

**Ferrous Metal:**

1 Coat: Valspar® Anti-Rust Armor Primer

1–2 Coats: Contractor Coat Int/Ext Alkyd Gloss

**Masonry:**

1 Coat: Valspar® Masonry and Stucco Primer

1–2 Coats: Contractor Coat Int/Ext Alkyd Gloss

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Alkyd resin

**Pigment Type:** Titanium Dioxide

**Viscosity:** 75–85 Krebs Units

**Sheen:** 80 + Units @ 60° angle

**Flashpoint:** 101 °F

**VOC:** < 380 g/L – 3.17 lb/gal as per 40 CFR 59.406

**VOC (lbs./gal.):** 3.1

**Volume Solids:** 53%

**Weight Solids:** 68%

**Weight Per Gallon:** 9.73 lbs. /gal.

**Practical Coverage:** Covers up to 350–450 sq. ft. per gallon (32–42 m<sup>2</sup> per 3.78 L) depending on surface porosity. Do not thin.

**Recommended Film Thickness:**

4.0 mil Wet      2.0 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To The Touch:** 6–8 hours

**Recoat:** 24 hours

**Washing Instructions:** Wait 7 days before

washing with a mild detergent and soft sponge.

**Application Temperature:** 50–90°F (10–32°C)

**Storage Temperature:** 40–90°F (5–32°C)

### REGULATORY COMPLIANCE

Current as of: 6/5/2018

SCAQMD	No
CARB 2000 SCM	No
CARB 2007 SCM	No
OTC/LADCO	No
US National	Yes

### CLEANUP AND DISPOSAL

Clean up with mineral spirits or VOC-compliant brush cleaner. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

**Danger:** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed, water-filled metal container. Dispose of according to local regulations.

# valsparPRO™ Valspar® 4000 Int/Ext Alkyd Semi-Gloss

---

## No. 9451858 Series

### SURFACE PREPARATION

#### **General:**

Read the Lead Warning paragraph. Clean the surface thoroughly to remove surface contamination, mildew, stains and rust with an appropriate cleaner. Scrape off any loose or peeling paint. Spot prime when needed. Dull glossy surfaces with light sanding. Prime with appropriate Valspar® Primer.

#### **Clean mildew from the surface:**

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

#### **Drywall:**

Fill cracks, pits and voids with patching compound, let cure and sand smooth. Remove all sanding dust. Prime new drywall with a Valspar® Interior Latex Primer.

#### **Plaster:**

Allow new plaster to fully cure and sand smooth. Remove all sanding dust. New plaster must be primed with a Valspar® Interior Latex Primer.

#### **Wood:**

Sand wood smooth and patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. New or bare surfaces must be primed with an appropriate Valspar® primer.

#### **Concrete/Masonry:**

New concrete, masonry surfaces and mortar should be cured, usually 30 days. Remove all form release or curing agents. Remove all loose material or dust. Soft concrete or masonry surfaces should be primed with a Valspar® Latex Primer.

#### **Metal:**

Hand or power tool clean steel to remove loose mill scale and rust. Remove oily residues and contaminants with solvent or appropriate cleaning solution. Change rags often, to assure that residual contaminants are completely removed. Prime with Valspar® Armor Anti-Rust Primer.

### LEAD WARNING

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### LIMITED WARRANTY

This product is warranted to meet the application, appearance and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions, and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT, AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights that vary from state to state.

**CONTRACTOR AND COMMERCIAL CUSTOMERS:** When used for commercial or nonresidential applications, this product is warranted to perform as indicated on the product label and to be free of material defects. At its option, Valspar will replace or refund the original purchase price of this product if it does not perform as labeled or is proven to be defective. All other warranty terms above apply.

### CAUTIONS

**DANGER!** HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE! VAPOR HARMFUL. IRRITATES EYES, SKIN AND RESPIRATORY TRACT.

Contains Aliphatic Hydrocarbons. Contents are **COMBUSTIBLE**. Keep away from heat and open flame. **VAPOR HARMFUL**. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

26 (01/10)

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:**  
1-888-345-5732

Cleveland, OH  
44115

888.313.5569  
valsparpaint.com

Revised: 11/19/2020  
VAL4000INTALKSG