



# Valspar® Multi-Surface Primer & Sealer

## GENERAL DESCRIPTION

Valspar® Multi-Surface Primer will improve the performance of your topcoat, improving sheen differences between porous and non-porous surfaces and allowing color uniformity. This zero VOC\* formula provides an excellent base coat for professionals and homeowners no matter the sheen or paint choice. This Valspar® product offers good hide, can be recoated in just 2 hours and is ideal for drywall, wood and masonry.

## PRODUCT FEATURES

- Good Hide
- Improves Topcoat Performance
- Zero VOC
- GREENGUARD Certified
- Recoat in 2 hours
- Ideal for sealing porous surfaces
- Works with all paint sheens
- Works on all topcoats
- Great for brush, roller and spray application
- May be used as packaged or tinted

## WHERE TO USE

Properly prepared interior walls, ceilings and trim, including plaster, wood, drywall, brick and cement. Do not use on bare metal or over glazed or glossy surfaces.

## SHIPPING AND PACKAGING

### Freight Classification:

Paint or paint related material. Protect from freezing.

### Packaging:

Gallon – 4 per carton  
5 gallon pail

## COMPOSITION

### Base and Fill Levels

(L/gal.)

3.78

White

(0083179, 0083180)

## APPLICATION

Stir thoroughly. Internix containers to ensure uniform colour. Apply with a premium-quality roller, premium-quality synthetic brush or airless sprayer. If applying by spray, back-roll or back-brush to work paint into the surface. Apply a liberal coat of primer uniformly, working well into the surface. Use up to 60 mL (2 fl. oz.) colourant per gallon.

**Airless Spray:** Pressure: 2000 PSI

**Tip:** 0.015–0.019"

**Brush:** premium-quality synthetic brush

**Roller:** premium quality

## SYSTEM

## RECOMMENDATIONS

### Drywall:

1 Coat Valspar® Multi-Surface Primer / Sealer  
1-2 Coats Valspar® Paint

### Plaster:

1 Coat Valspar® Multi-Surface Primer / Sealer  
1-2 Coats Valspar® Paint

### Wood:

1 Coat Valspar® Multi-Surface Primer / Sealer  
1-2 Coats Valspar® Paint

### Masonry:

1 Coat Valspar® Multi-Surface Primer / Sealer  
1-2 Coats Valspar® Paint

### Brick:

1 Coat Valspar® Multi-Surface Primer / Sealer  
1-2 Coats Valspar® Paint

**Note:** If using over stained areas, allow to dry 4 hours, apply test area with preferred topcoat. If bleeding occurs use Valspar® Stain Stopper, Valspar® Bonding Primer or other appropriate stain-blocking primer.

## PRODUCT SPECIFICATIONS

**Vehicle Type:** Vinyl Acetate Ethylene Copolymer

**Pigment Type:** Titanium dioxide

**Viscosity:** 99-105 Krebs Units

**Sheen:** 0–9 Units @ 85° angle

**Flashpoint:** N/A

**VOC:** < 50 g/L as per 40 CFR 59.406

**Volume Solids:** 25.7%

**Weight Solids:** 42.5%

**Weight Per Gallon:** 4.9 kg

**Practical Coverage:** Up to 37 m<sup>2</sup> per 3.78 L (400 sq. ft. per gallon) depending on surface porosity.

**Recommended Film Thickness:**

4.0 mil Wet      1 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To Touch:** 1 hour

**Recoat:** 2 hours for latex  
4 hours for oil

**Washing Instructions:** Wait at least 7 days before washing with a mild detergent and soft sponge

**Application Temperature:** 10–32 °C (50–90 °F)

**Storage Temperature:** 5–32 °C (40–90 °F)

## REGULATORY COMPLIANCE

Current as of: 10/20/2020

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes



## **SURFACE PREPARATION**

Surfaces must be clean, dry and dull prior to application. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. All dust should be removed.

**Drywall:** Fill cracks and holes with joint compound and sand smooth.

**Wood:** Sand to a fresh surface. Patch imperfections with wood filler. Heavily stained areas, including tannin stains on wood, may require an appropriate stain-blocking primer.

**Plaster:** Must be dry, fully cured and in good condition. Remove all chalky residue.

**Concrete/Masonry:** Must be dry, fully cured and in good condition. Remove any powdery dust and efflorescence. Fill the pores of concrete block with a latex block filler. Soft concrete or masonry should be primed with a masonry conditioner.

## **LEAD WARNING**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting your local health authority.

## **LIFETIME LIMITED**

### **WARRANTY**

1. Warranty: If this product fails to perform to your satisfaction at the time of application, when applied to a properly prepared residential surface in accordance with the label directions, return it to the store with your proof-of-purchase for either replacement of an equivalent quantity of product free of charge or for a refund of the original purchase price.

2. Exclusions: This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product. **EXCEPT IF YOU PURCHASED THE PRODUCT AS A CONSUMER RESIDING IN THE PROVINCE OF QUEBEC, IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES AND CONDITIONS, INCLUDING WARRANTIES AND CONDITIONS OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.**

## **MILDEW**

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

## **CLEANUP/STORAGE/ DISPOSAL**

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

## **CAUTIONS**

MAY IRRITATE EYES. Do not get in eyes. Keep out of reach of children. **FIRST AID TREATMENT:** Contains: surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

Valspar, Cleveland, Ohio 44115  
1-800-785-1276  
valspar.ca  
Revised: 5/9/23  
VALCMSP  
Version: 2