

GENERAL DESCRIPTION

Valspar® High Hiding Primer provides ease when drastically changing colours by hiding the previous colour with one coat. It will also provide uniformity between porous and non-porous surfaces when patching is necessary. This Valspar® product is an excellent base coat; it can lock in minor stains and also works well with all paint sheens.

PRODUCT FEATURES

- Improves Topcoat Uniformity
- Hides Previous Colour With One Coat
- Green Guard Certified
- Ideal for colour changes
- Recoat in 2 hours with latex paint
- Works with all paint sheens
- Use on drywall, wood, plaster and masonry
- Locks in minor stains

WHERE TO USE

Properly prepared interior walls, ceilings and trim, including plaster, wood, drywall, brick and cement. Do not use on bare metal or over glazed or glossy surfaces.

SHIPPING AND PACKAGING

Freight Classification:

Paint or paint related material. Protect from freezing.

Packaging:

Quart – 4 per carton
Gallon – 4 per carton
5 gallon pail

COMPOSITION

Base and Fill Levels

(L/gal.)

3.78

White

(0164759, 0168215,
0170071)

APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform colour. Apply with a premium-quality roller, premium-quality synthetic brush or airless sprayer. If applying by spray, back-roll or back-brush to work paint into the surface. Apply a liberal coat of paint uniformly, working well into the surface. Use up to 60 mL (2 fl. oz.) colourant per gallon.

Airless Spray: Pressure: 2000 PSI

Tip: 0.015–0.019"

Brush: premium-quality synthetic brush

Roller: premium quality

SYSTEM

RECOMMENDATIONS

Drywall:

1 Coat Valspar® High-Hiding Primer / Sealer

1-2 Coats Valspar® Paint

Plaster:

1 Coat Valspar® High-Hiding Primer / Sealer

1-2 Coats Valspar® Paint

Wood:

1 Coat Valspar® High-Hiding Primer / Sealer

1-2 Coats Valspar® Paint

Masonry:

1 Coat Valspar® High-Hiding Primer / Sealer

1-2 Coats Valspar® Paint

Brick:

1 Coat Valspar® High-Hiding Primer / Sealer

1-2 Coats Valspar® Paint

Previously painted surfaces:

1 Coat Valspar® High-Hiding Primer / Sealer

1-2 Coats Valspar® Paint

Note: If using over stained areas, allow to dry 4 hours, apply test area with preferred topcoat. If bleeding occurs use Valspar® Stainblocking Bonding Primer or other appropriate stain-blocking primer.

PRODUCT SPECIFICATIONS

Vehicle Type: Vinyl Acetate Ethylene Copolymer

Pigment Type: Titanium dioxide

Viscosity: 105-111 Krebs Units

Sheen: 0–5 Units @ 85° angle

Flashpoint: N/A

VOC: < 50 g/L as per 40 CFR 59.406

Volume Solids: 29%

Weight Solids: 46%

Weight Per Gallon: 4.99 kg

Practical Coverage: up to 37 m² per 3.78 L (400 sq. ft. per gallon) depending on surface porosity.

Recommended Film Thickness:

4.0 mil Wet

1.2 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

To Touch: 1 hour

Recoat: 2 hours for latex

4 hours for oil

Washing Instructions: Wait at least 7 days before washing with a mild detergent and soft sponge.

Application Temperature: 10–32 °C (50–90 °F)

Storage Temperature: 5–32 °C (40–90 °F)

REGULATORY COMPLIANCE

Current as of: 10/20/2020

SCAQMD Yes

CARB 2000 SCM Yes

CARB 2007 SCM Yes

OTC/LADCO Yes

US National Yes



SURFACE PREPARATION

Surfaces must be clean, dry and dull prior to application. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. All dust should be removed.

Drywall: Fill cracks and holes with joint compound and sand smooth.

Plaster, Masonry, Block: New surfaces must cure at least 30 days. Fill rough surfaces if desired.

Wood: Sand to a fresh surface. Patch imperfections with wood filler. Heavily stained areas, including tannin stains on wood, may require an appropriate stain-blocking primer.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting your local health authority.

LIFETIME LIMITED WARRANTY

1. Warranty: If this product fails to perform to your satisfaction at the time of application, when applied to a properly prepared residential surface in accordance with the label directions, return it to the store with your proof-of-purchase for either replacement of an equivalent quantity of product free of charge or for a refund of the original purchase price.

2. Exclusions: This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product. **EXCEPT IF YOU PURCHASED THE PRODUCT AS A CONSUMER RESIDING IN THE PROVINCE OF QUEBEC, IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES AND CONDITIONS, INCLUDING WARRANTIES AND CONDITIONS OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.**

CLEANUP/STORAGE/ DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of container and/or unused contents in accordance with local, municipal, or provincial regulations.

CAUTIONS

MAY IRRITATE EYES. Do not get in eyes. Keep out of reach of children. **FIRST AID TREATMENT:** Contains: surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

Valspar, Cleveland, Ohio 44115
1-800-785-1276
valspar.ca
Revised: 5/9/23
VALCHHP
Version: 2