



Anti-Skid Floor Texture Additive

82795

GENERAL DESCRIPTION

Valspar Anti-Skid Floor Texture Additive, when mixed with sealers, floor paint, or epoxies enhances traction on concrete, wood, metal or fiberglass surfaces. Anti-Skid Additive will not change the color, properties or performance of the coating. Particularly valuable in areas used by children and the elderly, or areas subject to snow, rain or other wet conditions.

PRODUCT FEATURES

- Enhances traction
- Creates a skid-resistant surface

RECOMMENDED USES

- Stairs, ramps, garages, pool areas, porches, walkways, patios and decks

STORAGE AND DISPOSAL

Unused additive and the container may be thrown away. Do not reuse container.

COMPOSITION

Package
Fill

Anti-Skid additive 3 oz

APPLICATION

Mix 1.5 oz. (1/2 of this pouch) of Anti-Skid Floor Texture Additive per gallon of paint or stain. For added anti-skid properties, use 3 oz. (entire pouch) per gallon of paint or stain. Add slowly while stirring and mix thoroughly before and during use.

LIMITED WARRANTY

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

CAUTIONS

CAUTION! EYE IRRITANT

CAUTION: MAY CAUSE EYE, SKIN, NOSE, AND THROAT IRRITATION.

Use only with adequate ventilation. Avoid breathing powder by wearing an appropriate particulate respirator. Avoid contact with eyes and skin. Wear protective glasses, gloves, and other appropriate clothing. Loose, dry material may create a slip hazard. Sweep up and place in appropriate disposal container. Close container after use. Wash thoroughly after handling.

FIRST AID:

EYES: Flush eyes immediately with water for at least 15 minutes. Contact a physician.

SKIN: Wash thoroughly with soap and water. Contact a physician if irritation persists.

INGESTION: If swallowed, induce vomiting. Contact a physician.

INHALATION: Remove to fresh air. Contact a physician if irritation persists.

**KEEP OUT OF THE REACH OF CHILDREN.
DO NOT TAKE INTERNALLY**

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

1191 Wheeling Road, Wheeling, IL 60090
888.313.5569
www.valsparpaint.com
Revised: Sept 2012