



Valspar® Oil Stain Remover

No. 82799

GENERAL DESCRIPTION

Oil Stain Remover quickly and easily absorbs and lifts stains from concrete without scrubbing. It's an important preparatory component to any concrete painting or staining project.

PRODUCT FEATURES

- Absorbs and lifts oil stains without scrubbing

RECOMMENDED USES

For use on concrete only. Most commonly used on concrete driveways, garages, patios and walkways.

STORAGE AND DISPOSAL

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

APPLICATION AND CLEANUP

SHAKE WELL BEFORE USE. Always test a small area before use. Do not use on wet surfaces. For best performance, use when temperature is above 60 °F (16 °C).

1. Scrape off buildup and sweep area.
2. Apply to stain, starting one inch beyond perimeter and working toward the center.
3. Allow 5–8 hours to dry.
4. Sweep up powder.
5. Immediately rinse the area with a strong stream of water.
6. Provide adequate ventilation and allow moisture to evaporate. If stain remains, reapply, scrub with stiff-bristled brush and repeat steps 3 thru 6.

LIMITED WARRANTY

This product is warranted to be free of defects and to be of merchantable quality. If you are not satisfied, return to the place of purchase with the unused portion and the original sales receipt. If the product is found to be defective, you will receive a replacement of the defective product or, at our option, a full refund. This limited warranty is your only warranty and excludes labor costs or any other incidental or consequential damages. Application of any replacement product is your responsibility. This warranty gives you specific legal rights and you may have other legal rights which vary from state to state.

PRODUCT SPECIFICATIONS

VOC (g/L): less than 4% VOC

Practical Coverage: Treats 24 sq. ft. per gallon when spread using 1/4" V-notched spreader.

CAUTIONS

WARNING! COMBUSTIBLE LIQUID AND VAPOR.

WARNING! CONTAINS D-LIMONENE. KEEP OUT OF THE REACH OF CHILDREN. Causes eye, skin, nose and throat irritation. May cause allergic skin reaction. **USE ONLY WITH ADEQUATE VENTILATION.** Keep away from heat, sparks and flame. **AVOID CONTACT WITH EYES, SKIN AND CLOTHING.** Wash thoroughly after use. Close container after each use. **DO NOT TAKE INTERNALLY. FIRST AID: EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.* **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **IF SWALLOWED:** Do not induce vomiting. Get medical attention immediately.*

* Call poison control center, hospital emergency room or physician immediately.

CS 1.3 DL

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631

877.825.7727

valsparpaint.com

Revised: 5/15/14

Version: 82799A