

### GENERAL DESCRIPTION

Valspar® Stainblocking Bonding Primer is a high-quality latex primer providing extreme adhesion over glossy surfaces. This product is ideal for cabinets, tile, trim, doors, glass, metal, drywall, wood, masonry, and paneling. It also blocks common household stains as well as stains from tannin bleed. This Valspar® product dries in 30 minutes for a quick recoat time. It works well with all paint sheens to improve topcoat uniformity and is sandable for a smooth finish.

### PRODUCT FEATURES

- Blocks Stains and Offers Mildew-Resistant Finish
- Extreme adhesion
- Dries in 30 minutes
- Ideal for cabinets, tile, trim, doors, glass, metal, drywall, wood, masonry and paneling
- Blocks stains
- Offers mildew-resistant finish
- Recoat in 30 minutes
- Sandable for smooth finish
- Improves topcoat uniformity
- Works with all paint sheens
- Blocks tannin stains
- May be used as packaged or tinted

### WHERE TO USE

Properly prepared interior and exterior glossy surfaces, including ceramic tile, cabinets, galvanized metal and aluminum.

### SHIPPING AND PACKAGING

#### **Freight Classification:**

Paint or paint related material. Protect from freezing.

#### **Packaging:**

Quart- 4 per carton  
Gallon – 4 per carton

### COMPOSITION

#### **Base and Fill Levels**

(L/gal.)

**White**  
(0876240, 0499418)

3.78

### APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform colour. Apply with a premium-quality roller, premium-quality synthetic brush or airless sprayer. If applying by spray, back-roll or back-brush to work paint into the surface. Apply a liberal coat of paint uniformly, working well into the surface. Use up to 60 mL (2 fl. oz.) colourant per gallon.

**Airless Spray:** Pressure: 2000 PSI

**Tip:** .015–0.021"

**Brush:** premium-quality synthetic brush

**Roller:** premium quality

### SYSTEM

### RECOMMENDATIONS

#### **Drywall:**

1 Coat Valspar® Stainblocking Bonding Primer / Sealer

1-2 Coats Valspar® Paint

#### **Wood:**

1 Coat Valspar® Stainblocking Bonding Primer / Sealer

1-2 Coats Valspar® Paint

#### **Plaster:**

1 Coat Valspar® Stainblocking Bonding Primer / Sealer

1-2 Coats Valspar® Paint

#### **Masonry:**

1 Coat Valspar® Stainblocking Bonding Primer / Sealer

1-2 Coats Valspar® Paint

#### **Tile/Glass:**

1 Coat Valspar® Stainblocking Bonding Primer / Sealer

1-2 Coats Valspar® Paint

#### **Galvanized Metal/Aluminum:**

1 Coat Valspar® Stainblocking Bonding Primer / Sealer

1-2 Coats Valspar® Paint

#### **Previously Painted Surfaces:**

1 Coat Valspar® Stainblocking Bonding Primer / Sealer

1-2 Coats Valspar® Paint

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Styrene Acrylic Copolymer

**Pigment Type:** Titanium dioxide

**Viscosity:** 98-104 Krebs Units

**Sheen:** 0–10 Units @ 85° angle

**Flashpoint:** N/A

**VOC:** < 50 g/L as per 40 CFR 59.406

**Volume Solids:** 43%

**Weight Solids:** 60%

**Weight Per Gallon:** 5.35 kg

**Practical Coverage:** Up to 37 m<sup>2</sup> per 3.78 L (400 sq. ft. per gallon) depending on surface porosity.

**Recommended Film Thickness:**

4.0 mil Wet

1.7 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To Touch:** 30 minutes

**Recoat:** 2 hours with latex

4 hours with oil

**Washing Instructions:** Wait at least 7 days before washing with a mild detergent and soft sponge

**Application Temperature:** 10–32 °C (50–90 °F)

**Storage Temperature:** 5–32 °C (40–90 °F)

### REGULATORY COMPLIANCE

Current as of: 10/20/2020

SCAQMD Yes

CARB 2000 SCM Yes

CARB 2007 SCM Yes

OTC/LADCO Yes

US National Yes

### SURFACE PREPARATION

Thoroughly clean the surface and allow to dry. Remove all dirt, dust, chalk, rust, grease, wax and mildew. Scrape off loose and peeling paint. Thoroughly remove chalk by vigorous washing, then rinse. Bonds to clean, glossy surfaces. No need to remove gloss from shiny surfaces. Countersink nails and apply an oil-based metal primer to exposed nail heads. Caulk cracks and joints.

**Bare Wood:** Remove sap from knots and sappy areas.

**Masonry:** Brush loose sand, dust and other material from the surface.

**Metal:** New galvanized surfaces should be allowed to age 6 months before painting. All bare iron and steel surfaces should be primed with a rust-inhibitive metal primer.

**New Fibre Cement Board:** Wash thoroughly and allow to dry before priming.

### LEAD WARNING

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting your local health authority.

### LIFETIME LIMITED

#### WARRANTY

Warranty: If this product fails to perform to your satisfaction at the time of application, when applied to a properly prepared residential surface in accordance with the label directions, return it to the store with your proof-of-purchase for either replacement of an equivalent quantity of product free of charge or for a refund of the original purchase price.

2. Exclusions: This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product. **EXCEPT IF YOU PURCHASED THE PRODUCT AS A CONSUMER RESIDING IN THE PROVINCE OF QUEBEC, IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES AND CONDITIONS, INCLUDING WARRANTIES AND CONDITIONS OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.**

### MILDEW

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

### CLEANUP/STORAGE/

#### DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of container and/or unused contents in accordance with local, municipal, or provincial regulations.

### CAUTIONS

MAY IRRITATE EYES. Do not get in eyes. Keep out of reach of children. **FIRST AID TREATMENT:** Contains: surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

Valspar, Cleveland, Ohio 44115  
 1-800-785-1276  
 valspar.ca  
 Revised: 5/9/23  
 VALCSBP  
 Version: 2