

### GENERAL DESCRIPTION

Valspar® High Gloss Enamel Paint + Primer is ideal for both interior and exterior use. It features a Gloss-Lock formula, ensuring that it will maintain a freshly painted finish, even after cleaning. This stain resistant and scrubbable coating provides a durable, lustrous finish that is burnish resistant to always retain it's glossy finish.

### PRODUCT FEATURES

- Durable, Lustrous Finish
- Withstands Wear, Indoors and Out
- Excellent Hide & Silky Smooth Appearance
- Stain resistant and scrubbable
- Burnish resistant to retain glossy finish
- Provides a mildew-resistant finish
- 100% acrylic latex
- Lifetime limited warranty

### WHERE TO USE

Properly prepared interior and exterior surfaces, including trim, ceilings, drywall, plaster, primed metal, wood, brick and masonry.

### SHIPPING AND PACKAGING

#### **Freight Classification:**

Paint or paint related material. Protect from freezing.

#### **Packaging:**

Quart – 4 per carton  
Gallon – 4 per carton

### COMPOSITION

	Base and Fill Levels (L/gal.)
<b>Ultra White</b> (0555045, 0555044)	3.78
<b>Base C</b> (0833125, 0833124)	3.43

### APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 10-32°C (50-90°F). Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, 0.015-0.019" tip). Thinning not required. Paint the ceiling first, then walls and trim. For roller application, cover approximately a 61 x 61 cm (2' x 2') area using an "N" pattern. Finish with light roller strokes in one direction. Certain deep or bright colours may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

**Airless Spray:** Pressure: 2000 PSI

**Tip:** 0.015–0.019"

**Brush:** premium-quality brush

**Roller:** premium quality synthetic

### System Recommendations

#### **Plaster:**

2 Coats: Valspar® High-Gloss Enamel

#### **Wood:**

2 Coats: Valspar® High-Gloss Enamel

#### **Brick:**

2 Coats: Valspar® High-Gloss Enamel

#### **Drywall:**

2 Coats: Valspar® High-Gloss Enamel

#### **Cement:**

2 Coats: Valspar® High-Gloss Enamel

#### **Metal:**

1 Coat: Anti-Rust Primer

1 Coat: Valspar® High-Gloss Enamel

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic

**Pigment Type:** Titanium Dioxide

**Viscosity:** 94-100 Krebs Units

**Gloss:** >60 Units @ 60° angle

**Flashpoint:** N/A

**VOC (g/L):** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

**Volume Solids:** 35.1%

**Weight Solids:** 47.8%

**Weight Per Gallon:** 4.67 kg

**Practical Coverage:** 37 m<sup>2</sup> per 3.78 L (300-400 sq. ft. per gallon) depending on surface porosity. Do not thin.

#### **Recommended Film Thickness:**

4.0 mil Wet

1.4 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To The Touch:** 1 hour

**Recoat:** 2-4 hours

**Application Temperature:** Apply product when surface, air and product temperatures are between 10-32°C (50-90°F)

### **SURFACE PREPARATION**

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull.

**Drywall:** Fill cracks and holes with patching paste and sand smooth.

**Plaster, Masonry, Block:** New surfaces must cure at least 30 days. Fill rough surfaces if desired.

**Wood:** Sand to a fresh surface. Patch imperfections with wood filler.

**Priming:** This paint can be used to prime patched areas and bare surfaces before applying the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic colour changes or deep, vivid colours, prime with an appropriate tintable primer for optimal colour accuracy and coverage.

### **LEAD WARNING**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting your local health authority.

### **LIFETIME LIMITED**

#### **WARRANTY**

1. If this product, when applied and maintained according to product application and maintenance instructions to a properly prepared surface, fails to perform to your complete satisfaction, for as long as you own your home, return it to the store with your proof of purchase for your choice of either replacement of an equivalent quantity of product free of charge or for a refund of the original purchase price.

2. This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product.

3. Your sole remedy, and Valspar's sole liability, under this warranty is the replacement of product or refund and does not include labour or costs associated with the application or removal of any product.

4. **IN NO EVENT SHALL THE VALSPAR BE LIABLE, UNLESS YOU PURCHASED THE PRODUCT AS A CONSUMER IN THE PROVINCE OF QUÉBEC, FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES AND CONDITIONS OF SALE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.**

5. Some provinces do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from province to province.

### **MILDEW**

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

### **CLEANUP/STORAGE/**

#### **DISPOSAL**

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

### **CAUTIONS**

MAY IRRITATE EYES. Do not get in eyes. Keep out of reach of children. **FIRST AID TREATMENT:** Contains: surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

Valspar, Cleveland, Ohio 44115

1-800-785-1276

valspar.ca

Revised: 5/9/23

VALCHG

Version: 2