



Valspar® Colour-Changing Ceiling Paint + Primer

GENERAL DESCRIPTION

Valspar® Colour-Changing Ceiling Paint + Primer offers a flat finish that covers imperfections in just one coat. This spatter resistant formulas also features disappearing purple technology, meaning that the paint will appear purple when you paint but dry ultra white. This ensures that you never miss a spot when using this Valspar® product.

PRODUCT FEATURES

- Never Miss A Spot
- Flat Finish Covers Imperfections In One Coat
- Spatter Resistant Formula

WHERE TO USE

Properly prepared and durable textured or plain interior ceilings, including previously painted and primed plaster, drywall and acoustical tile. See **Surface Preparation** for “blown-on” soft-fibred ceilings surfaces.

SHIPPING AND PACKAGING

Freight Classification:

Paint or paint related material. Protect from freezing.

Packaging:

Gallon

COMPOSITION

Base and Fill Levels

(L/gal.)

3.78

White

(0555036)

APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 10-32°C (50-90°F). Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, 0.015-0.019" tip). Thinning not required. Paint the ceiling first, then walls and trim. For roller application, cover approximately a 61 x 61 cm (2' x 2') area using an “N” pattern. Finish with light roller strokes in one direction. Certain deep or bright colours may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

Airless Spray: Pressure: 2000 PSI

Tip: 0.015–0.019”

Brush: premium-quality brush

Roller: premium quality synthetic

SYSTEM

RECOMMENDATIONS

Bare Drywall and Plaster:

2 Coats: Valspar Colour Changing Ceiling Paint

Stains:

1 Coat: Valspar Bonding Stainblocking Primer Sealer

1–2 Coats: Valspar Colour Changing Ceiling Paint

Acoustical Tile:

1–2 Coats: Valspar Colour Changing Ceiling Paint

“Blown-on” Soft-Fibred Ceilings:

1 Coat: Appropriate interior oil primer

1–2 Coats: Valspar Colour Changing Ceiling Paint

Previously Painted Surfaces:

1–2 Coats: Valspar Colour Changing Ceiling Paint

PRODUCT SPECIFICATIONS

Vehicle Type: Vinyl Acrylic

Viscosity: 95-105 Krebs Units

Sheen: 0-5 units at 85°

Flashpoint: N/A

VOC (g/L): < 50 g/L 0.42 lb./gal as per 40 CFR 59.406

Weight Per Gallon: 5 kg

Volume Solids: 33.7%

Weight Solids: 49.6%

Practical Coverage: Covers approximately 37 m² per 3.78 L (400 sq. ft. per gallon) depending on surface porosity. Significantly less on acoustical tile.

Recommended Film Thickness:

4.0 mils wet, 1.35 mils dry

Dry Time @ 77 °F and 50% Relative Humidity

To Touch: 30-60 min

Recoat: 2-4 hours

Application Temperature: 10–32 °C (50–90 °F)

Washing Instructions: Wait 7 days before washing with a mild detergent and soft sponge.

SURFACE PREPARATION

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Patch cracks and spot-prime. Remove gloss from shiny surfaces.

Acoustical Tile: Vacuum or dust tiles to remove embedded dust. To maintain the sound-absorbing qualities of the tile, do not use a primer. Apply ceiling paint directly to the tiles. Test vinyl-coated tiles to ensure adhesion. Do not attempt to fill or clog acoustical perforations.

“Blown-on” Soft-Fibred Ceilings: Caution! All water-based paints will loosen or deteriorate a “blown-on” soft-fibred ceiling surface and make for a difficult repair. If you are not sure about your ceiling texture type, apply to a small test area in a closet or other hidden spot. If deterioration occurs and if painting is necessary, priming with an oil-based primer may help minimize the deterioration. Do not use a latex primer.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting your local health authority.

LIFETIME LIMITED

WARRANTY

This warranty is made to you, the product purchaser who owns the property where the product is applied. This warranty is not transferable, except if a contractor purchased and applied the product to the property for you; in such a case, the warranty is transferable to you. If this product, when applied and maintained according to product application and maintenance instructions to a properly prepared surface, fails to perform to your complete satisfaction for as long as you own the property, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product. Your sole remedy, and Valspar's sole liability, under this warranty is the replacement of product or refund and does not include labour or costs associated with the application or removal of any product. **EXCEPT IF YOU PURCHASED THE PRODUCT AS A CONSUMER RESIDING IN THE PROVINCE OF QUEBEC, IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES AND CONDITIONS, INCLUDING WARRANTIES AND CONDITIONS OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.** Some provinces do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from province to province. www.valsparpaint.ca

CLEANUP/STORAGE/

DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of container and/or unused contents in accordance with local, municipal, or provincial regulations.

CAUTIONS

MAY IRRITATE EYES. Do not get in eyes. Keep out of reach of children. **FIRST AID TREATMENT:** Contains: surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

Valspar, Cleveland, Ohio 44115
1-800-785-1276
valspar.ca
Revised: 5/9/23
VALCCCCEIL
Version: 3