



# Valspar® The Perfect White® Satin Paint + Primer

## GENERAL DESCRIPTION

Valspar® The Perfect White® is a great grab and go option for anyone looking for a clean, pure white paint. This Valspar® product is ideal for both interior and exterior projects. It offers outstanding durability along with stain and weather resistance. The interior/exterior coating provides a high-quality finish that features excellent hide and coverage.

## PRODUCT FEATURES

- Outstanding Durability
- Stain and Weather Resistant
- High-Quality Finish
- Grab & go
- Excellent hide
- Stain resistant and scrubbable
- Provides a mold- and mildew-resistant finish
- 100% acrylic
- Lifetime limited warranty

## WHERE TO USE

Properly prepared interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement and metal. Properly prepared exterior wood and metal siding and trim including hardboard, fibre cement board, vinyl, primed metal, shakes, brick, cement, cinder block and stucco. Do not use on glazed brick, floors or steps.

## SHIPPING AND PACKAGING

### **Freight Classification:**

Paint or paint related material. Protect from freezing.

### **Packaging:**

Gallon – 4 per carton

## COMPOSITION

### **Base and Fill Levels**

White  
(0790217)

(L/gal.)  
3.78

## APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform colour. Apply with a premium-quality roller, polyester brush or airless sprayer. If applying by spray, back-roll or back-brush to work paint into the surface. Apply a liberal coat of paint uniformly, working well into the surface.

**Airless Spray:** Pressure: 2000 PSI

**Tip:** 0.015–0.019"

**Brush:** Premium-quality

**Roller:** Premium-quality

## SYSTEM

### RECOMMENDATIONS

#### **New Wood:**

2 Coats: Valspar® The Perfect White®

#### **Previously Paint Surfaces:**

2 Coats: Valspar® The Perfect White®

#### **Laminate:**

1 Coat: Valspar® Multi-Surface Primer

2 Coats: Valspar® The Perfect White®

For improved adhesion on extremely smooth surfaces use 1 coat of Valspar® Stainblocking Bonding Primer

Recommended one coat of primer if the painting project requires a bold transition. This will improve the topcoat hiding power.

## PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic resin

**Viscosity:** 95–100 Krebs Units

**Sheen:** 20–30 Units @ 85° angle

**Flashpoint:** 96.11 °C

**VOC:** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

**Volume Solids:** 40%

**Weight Solids:** 50%

**Weight Per Gallon:** 4.75 kg

**Practical Coverage:** Covers approximately 27–37 m<sup>2</sup> per 3.78 L (300–400 sq. ft. per gallon) depending on surface porosity. Do not thin.

#### **Recommended Film Thickness:**

4.0 mil Wet      1.6 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To The Touch:** 1 hour

**Recoat:** 4 hours

**Application Temperature:** 10–32 °C (50–90 °F)

**Storage Temperature:** 5–32 °C (40–90 °F)

**Washing Instructions:** Wait 7 days before washing with a mild detergent and soft sponge.

## LEAD WARNING

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting your local health authority.

### SURFACE PREPARATION

**Interior Surface Preparation:** Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Remove gloss from shiny surfaces. Patch cracks and spot-prime. This paint can be used to prime patched areas and bare surfaces before applying the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic colour changes or deep, vivid colours, prime with an appropriate tintable primer for optimal colour accuracy and coverage.

**Exterior Surface Preparation:** Thoroughly clean the surface and allow to dry. Remove all dirt, dust, chalk, rust, grease, wax and mildew. Previously Painted Surfaces (Including Painted Metal Siding): Scrape off loose and peeling paint, sand smooth, then spot-prime. Thoroughly remove chalk by vigorous washing, then rinse. Remove gloss from shiny surfaces. Countersink nails and apply an oil-based metal primer to exposed nail heads. Caulk cracks and joints. Bare Wood: Remove sap from knots and sappy areas. Spot prime with a stain-blocking primer/sealer. Prime entire area with a latex or oil-based exterior primer. Vinyl Siding: Wash thoroughly and allow to dry. Paint with a colour lighter than original siding colour.

**WARNING—** Painting with darker colours will cause warping or deformation from heat absorption. Hardboard Siding (Unprimed, Primed or Previously Painted): Remove any wax from bleed-through areas by wiping with rags soaked with mineral spirits. Turn rags often to avoid merely spreading wax around. Prime all hardboard with an exterior oil primer. Masonry: Brush loose sand, dust and other material from the surface. Metal: New galvanised surfaces should be allowed to age 6 months before painting. New Fibre Cement Board: Wash thoroughly and allow to dry. Prime with premium-quality 100%-acrylic exterior latex primer.

### LIFETIME LIMITED

#### WARRANTY

1. If this product, when applied and maintained according to product application and maintenance instructions to a properly prepared surface, fails to perform to your complete satisfaction, for as long as you own your home, return it to the store with your proof of purchase for your choice of either replacement of an equivalent quantity of product free of charge or for a refund of the original purchase price.

2. This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product.

3. Your sole remedy, and Valspar's sole liability, under this warranty is the replacement of product or refund and does not include labour or costs associated with the application or removal of any product.

4. IN NO EVENT SHALL THE VALSPAR BE LIABLE, UNLESS YOU PURCHASED THE PRODUCT AS A CONSUMER IN THE PROVINCE OF QUÉBEC, FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES AND CONDITIONS OF SALE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.

5. Some provinces do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from province to province. [www.valsparpaint.ca](http://www.valsparpaint.ca)

### MILDEW

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

### CLEANUP/STORAGE/ DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of container and/or unused contents in accordance with local, municipal, or provincial regulations.

### CAUTIONS

MAY IRRITATE EYES. Do not get in eyes. Keep out of reach of children. **FIRST AID TREATMENT:** Contains: surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

Valspar, Cleveland, Ohio 44115  
1-800-785-1276  
[valspar.ca](http://valspar.ca)  
Revised: 5/9/23  
VALCPWSAT  
Version: 2