

valspar® Valspar® Cabinet and Furniture Interior/Exterior Paint

No. 07401 Series

GENERAL DESCRIPTION

Valspar® Cabinet and Furniture Paint dries to a smooth factory-like finish and stands up to daily use leaving a fade-, scratch-, and scuff-resistant finish. Most projects will require little-to-no prep work. The oil-enriched formula provides exceptional durability with no brush marks.

PRODUCT FEATURES

- Oil-Enriched Enamel
- Strong, factory-like finish
- Fade-, scratch- & scuff-resistant
- No sanding or priming needed
- Soap-and-water cleanup
- Tintable to 1000+ colours

RECOMMENDED USES

Bare wood, previously painted wood or metal in sound condition, and properly prepared laminate.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

Quart – 4 per carton

Gallon – 4 per carton

COMPOSITION

Base and Fill Levels
(L/GAL)

3.66 Ultra White/Tint Base 1(740149, 740148)

3.43 Base 4 (740153, 740152)

APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform colour. Apply with a premium-quality roller or polyester brush. Two thin coats are required. Bare wood and some deep or bright colours may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage. Allow to dry thoroughly before recoating or use.

Airless Spray:

Pressure: 2000 PSI

Tip: .381–.4826mm

Brush: premium-quality polyester

Roller: premium-quality roller

SYSTEM RECOMMENDATIONS

Previously Painted Surfaces and New Wood:

2 Coats: Valspar® Cabinet and Furniture Paint

Laminate:

1 Coat: Valspar® Bonding Primer

2 Coats: Valspar® Cabinet and Furniture Paint

For improved adhesion on extremely smooth surfaces use 1 coat of Valspar® Bonding Primer

Recommended one coat of primer if the painting project requires a bold transition. This will improve the topcoat hiding power.

Metal:

1 Coat: Rust-Inhibitive Metal Primer

2 Coats: Valspar® Cabinet and Furniture Paint

PRODUCT SPECIFICATIONS

Vehicle Type: Waterborne Alkyd

Viscosity: 87-95 Krebs Units

Sheen: 45-55 at 85°

Flashpoint: N/A

VOC (g/L): < 50 g/L

Weight Per Gallon: 11.0 lbs.

Volume Solids: 33.8%

Weight Solids: 49.9%

Practical Coverage: Covers approximately 400 sq. ft. per gallon (37 m² per 3.78 L) depending on surface porosity.

Recommended Film Thickness:

4.0 mil Wet 1.3 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity To

Touch: 4 hours

Recoat: 8-12 hours

Cure Time: To prevent scratches, marring or peeling, allow the project to dry for a minimum of 3 days.

Application Temperature: 50–90 °F (10–32 °C)

*Data reported is typical of White and will vary by colour and batch.

REGULATORY COMPLIANCE

Current as of: 3/18/2020

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of container and/or unused contents in accordance with local, municipal, or provincial regulations.

valspar® Valspar® Cabinet and Furniture Satin Paint

No. 07401 Series

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Remove gloss from shiny surfaces. Patch cracks and spot prime prior to painting. For best results on heavily stained areas, apply one coat of an appropriate interior latex primer.

Previously Painted Surfaces and Bare Wood:

Thoroughly clean the surface and allow to dry. Remove all dirt, dust, chalk, rust, grease, wax and mildew. Scrape off loose and peeling paint. Dull glossy surfaces by sanding.

Metal:

Remove all oil, grease, dirt and oxidation from surface. All bare metal surfaces should be primed with a rust-inhibitive metal primer

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. For more information, contact your local health authority.

LIFETIME LIMITED WARRANTY

This warranty is made to you, the product purchaser who owns the property where the product is applied. This warranty is not transferable. If, however, a contractor purchased the product and applied it to your property, the warranty is transferable to you. This warranty is only valid when the product is applied to a properly prepared surface and maintained according to product application and maintenance instructions. If the product fails to perform in accordance with applicable product literature for as long as you own the property, Valspar shall, upon presentation of proof-of-purchase at the store where the product was purchased, replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect, damage or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or a defect in the underlying substrate, or improper application of the product. Your exclusive remedy and Valspar's sole liability under this warranty is the replacement of the product or a refund and does not include labor or costs associated with the application or removal of any product. **IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.** Some provinces do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from province to province. Valsparpaint.ca /1-877-VALSPAR

CAUTIONS

DANGER OF COMBUSTION. MAY IRRITATE EYES. Do not get in eyes. Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard. Dispose of in accordance with local fire regulations. Keep out of reach of children.

FIRST AID TREATMENT:

Contains: acrylic modified alkyd. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

Valspar
Mississauga, Ontario
Canada
Valsparpaint.ca
800.785.1276
Revised: 11/9/22
Version: VALCF