

GENERAL DESCRIPTION

Valspar® Door & Trim Oil-Enriched Enamel is an advanced technology water-based alkyd cross linking formula. It offers benefits of traditional alkyd and latex formulas.

PRODUCT FEATURES

BENEFITS SIMILAR TO ALKYD PAINTS:

- Superior flow and leveling leaving a smooth finish
- Hard, durable film

BENEFITS SIMILAR TO LATEX PAINTS:

- Easy soap and water cleanup
- Quick dry time which allows same day recoat and a quick tape time

GENERAL BENEFITS:

- Good block resistance, which minimizes doors and windows sticking to other painted surfaces
- Resists scuffs & scratches
- No sanding or priming needed

WHERE TO USE

- Bare wood
- Previously painted wood or metal in sound condition
- Properly prepared laminate

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

Quart – 4 per carton

COMPOSITION

Base and Fill Levels

(oz./gal.)

UW/Base 1
Base 4

31
29

APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller or polyester brush. **Note:** Two thin coats are required. Bare wood and some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage. Allow to dry thoroughly before recoating or use.

SYSTEM

RECOMMENDATIONS

Drywall/Plaster/Wood:

1 Coat: Valspar Interior Latex Primer
1-2 Coats: Valspar Door & Trim Oil-Enriched Enamel

Steel:

1 Coat: Valspar Acrylic DTM Primer
1-2 Coats: Valspar Door & Trim Oil-Enriched Enamel

Galvanized/Aluminum:

1 Coat: Valspar Bonding Primer
1-2 Coats: Valspar Door & Trim Oil-Enriched Enamel

Concrete:

1 Coat: Valspar Block Filler
1-2 Coats: Valspar Door & Trim Oil-Enriched Enamel

Masonry:

1 Coat: Valspar Alkali Resistant Primer
1-2 Coats: Valspar Door & Trim Oil-Enriched Enamel

Previously Painted Surfaces:

1-2 Coats: Valspar Door & Trim Oil-Enriched Enamel

PRODUCT SPECIFICATIONS

Vehicle Type: Water-Based Alkyd

Pigment Type: Titanium Dioxide

Viscosity: 94–100 Krebs Units

Sheen: 45-55 Units @ 60° angle

Flashpoint: N/A

VOC: < 50 g/L – 0.41 lb/gal as per 40 CFR 59.406

Volume Solids: 36%

Weight Solids: 53%

Weight Per Gallon: 11.2 lbs./gal.

Practical Coverage: Covers up to 100 sq. ft. per quart (9.3 m² per 946 mL). Do not thin.

Recommended Film Thickness:

4.0 mil Wet 1.4 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

To The Touch: 4 hours

Recoat: 8-12 hours

Application Temperature: 50–90 °F (10–32 °C)

Storage Temperature: 40–90 °F (5–32 °C)

CERTIFICATIONS

Current as of: April 2023

MPI #	N/A
MPI GPS 1	N/A
MPI GPS 2	N/A
LEED (US)	Yes
LEED (Canada)	Yes

REGULATORY COMPLIANCE

Current as of: April 2023

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

CLEANUP AND DISPOSAL

Clean up with soap and water. Do not freeze. Keep container closed when not in use. Do not transfer to other containers for storage or disposal. In case of spillage, absorb with inert material. Dispose in accordance with local, state and federal regulations.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. Remove rust, oil, grease, mildew salt and dirt from surface. Remove all dust or other loose material off the surface. Verify area is dry and free of all dust and loose material.

Previously painted surfaces and bare wood:

Thoroughly clean the surface and allow to dry. Remove all dirt, dust, chalk, rust, grease, wax and mildew. Scrape off loose and peeling paint. Dull previously coated surfaces by sanding for maximum performance.

Laminate: Apply a coat of bonding primer.

Bare metal: Apply a rust-inhibitive metal primer.

LIMITED WARRANTY

This product is warranted for your complete satisfaction for as long as you reside in your home. This warranty covers product that is applied to a properly prepared residential surface in accordance with label directions and excludes product failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

101 W Prospect Ave, Cleveland, OH 44115

valspar.com

Revised: 4/12/23