

GENERAL DESCRIPTION

Valspar® Porch, Floor and Patio Anti-Skid Enamel with HEAT RELIEF TECHNOLOGY™ adds traction to outdoor surfaces and delivers long-lasting weather protection. Engineered to create a UV-resistant shield that makes concrete and wood porches and patios cooler on hot days.

PRODUCT FEATURES

- HEAT RELIEF TECHNOLOGY™ creates a UV-resistant shield that makes concrete and wood porches and patios cooler on hot days and more comfortable to walk on.*
- 100% acrylic enamel
- Skid-resistant, textured coating increases traction for extra safety on steps, walkways and more
- Stands strong against wear and scratches
- Long-lasting weather protection for continued beauty and performance
- Available in most Valspar® colors
- Easy to apply, easy soap and water cleanup

*Reduces surface temperature when compared to bare concrete or wood. Amount of temperature reduction may differ due to: color choice, ambient temperature, time of day and the amount of direct sunlight on the surface.

RECOMMENDED USES

Great for use on properly prepared exterior concrete and wood such as porches, patios, stairs, breezeways, and outdoor floors. **Not for use on exterior wood decks, garage floors or other automobile parking areas.**

COMPOSITION

Base and Fill Levels

(oz./gal.)

Base 2 (83080)

126

Base 4 (83082)

116

APPLICATION AND CLEANUP

Mix well before and during use. If using more than one container, intermix all cans of the same color. Use a premium-quality, polyester brush for small area (stairs, etc.). For large areas, pour Valspar® Porch, Floor and Patio Anti-Skid Enamel with HEAT RELIEF TECHNOLOGY™ coating in a long, continuous bead across the "shorter side" of the surface. Spread the product uniformly with a premium-quality, 1/4" or 3/8" nap roller and finish with long, even strokes in one direction. After drying 24 hours, apply the second coat if necessary or desired, at a right angle to the first coat — again finishing with long, even strokes in one direction. Clean tools and hands with warm, soapy water. Discard used roller covers. Do not allow water to pond or puddle on newly painted surfaces.

Brush: Valspar® Wall and Trim 2 1/2"

Roller: Valspar® Textured Walls, Concrete & Decks 1/2" Nap

SLIP/SKIDRESISTANCE

Some surfaces may require a slip/skid resistant additive for safety. Surfaces may be slippery when wet and proper preventative precautions are recommended. To increase slip/skid resistance, add Valspar® Anti-Skid Floor Texture Additive to the coating when applying. See product data page for detailed instructions. The addition of anti-slip/skid additives will not eliminate the possibility or risk of slipping/skidding or falling.

TINTING

For best results use HEAT RELIEF color palette. Custom colors may not achieve full cooling benefit.

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic resin

Viscosity: 108–118 Krebs Units

Flashpoint: 205 °F

VOC (g/L): less than 50 g/L 0.42 lb/gal as per 40 CFR 59.406

VOC (lbs./gal.): 0.32

Volume Solids: 41%

Weight Solids: 60%

Weight Per Gallon: 12.1 lbs./gal.

Practical Coverage:

One gallon covers up to 100 ft² (9.3 m²), depending upon surface porosity. Thinning is not recommended.

Recommended Film Thickness:

18.0 mil Wet 7.4 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

Recoat: 24 hours

Light Foot Traffic: 24 hours

Normal Use: 48 hours for normal use

Washing: Allow at least 7 days before washing.

Use mild detergent and sponge.

Application Temperature: 50–90 °F (10–32 °C)

Storage Temperature: 40–90°F (5–32°C)

REGULATORY COMPLIANCE

Current as of: 9/12/2017

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. The surface must be clean, dry and free of all loose or peeling paint. Thoroughly clean surface and remove wax and grease with an all-purpose cleaner (TSP or substitute). Clean joints and cracks to remove all foreign material. Patch voids with appropriate crack patching material. Areas where ponding water is evident should be leveled prior to application.

Concrete:

New concrete, masonry surfaces and mortar should be cured 30 days. Remove all form release or curing agents. New, unpainted or smooth-worn concrete must be etched with a concrete cleaner, degreaser and etcher for proper penetration and adhesion with Valspar® Fast Prep Ready-to-Use Solution. Follow all label instructions. Remove all loose material or dust.

Wood:

Remove sap from knots and sappy areas. Rough or repaired wood surfaces should be sanded smooth. Prime bare, new wood with Valspar® Exterior Latex Primer.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

This product is warranted to perform to your satisfaction at the time of application when applied to a properly prepared residential surface in accordance with the label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. **THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

15 (1/10)

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

Product Information Hotline: 1-877-VALSPAR (825-7727)

Valspar, Cleveland, Ohio 44115
valsparpaint.com