



Valspar® Multi-Surface Interior Primer / Sealer

No. 0260948 series

GENERAL DESCRIPTION

Valspar® Multi-surface primer will create an optimal appearance for your topcoat, improving sheen differences between porous and non-porous surfaces and allowing color uniformity. This zero VOC* formula provides an excellent base coat for professionals and homeowners no matter the sheen or paint choice.

PRODUCT FEATURES

- Ideal for drywall, wood and masonry
- Good hide
- Improves topcoat performance
- Zero VOC*
- Works with all topcoats and paint sheens
- Great for brush, roller and spray application
- May be used as packaged or tinted

WHERE TO USE

Properly prepared interior drywall, plaster, wood, masonry, and metal surfaces.

SHIPPING AND PACKAGING

Freight Classification:

Paint or paint related material. Protect from freezing.

Packaging:

- 2740017 - Quart – 4 per carton
- 0260948 - Gallon – 4 per carton
- 0260949 - 5 Gallon Pail

COMPOSITION

Base and Fill Levels

(oz./gal.)

White 128

APPLICATION AND CLEANUP

Application:

Stir primer thoroughly before and during use. Apply with a premium-quality polyester brush, roller or airless sprayer. If applying by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface.

Cleanup:

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Airless Spray:

Pressure: 2000 PSI
Tip: 0.015–0.021"

Brush: Premium-quality nylon or polyester brush

Roller: Premium-quality synthetic, 3/8 – 1/2" nap

STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

PRODUCT SPECIFICATIONS

Vehicle Type: Vinyl Acetate Ethylene Copolymer

Pigment Type: Titanium dioxide

Viscosity: 99-105 Krebs Units

Sheen: 0–9 Units @ 85° angle

Flashpoint: N/A

VOC: < 100 g/L as per 40 CFR 59.406

Volume Solids: 25.7%

Weight Solids: 42.5%

Weight Per Gallon: 10.798 lbs./gal

Practical Coverage: up to 400 sq. ft. per gallon (37 m² per 3.78 L) depending on surface porosity.

Recommended Film Thickness:

4.0 mil Wet 1 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

To Touch: 1 hour

Recoat: 2 hours for latex

4 hours for oil

Washing Instructions: Wait at least 7 days before

washing with a mild detergent and soft sponge

Application Temperature: 50–90 °F (10–32 °C)

Storage Temperature: 40–90 °F (5–32 °C)

Tintable up to 2oz of Novo II black.

REGULATORY COMPLIANCE

Current as of: 10/20/2020

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

SURFACE PREPARATION

General:

Surfaces must be clean, dry and dull prior to application. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. All dust should be removed.

Drywall:

Fill cracks and holes with joint compound and sand smooth.

Plaster:

Must be dry, fully cured and in good condition. Remove all chalky residue.

*Zero VOC applies only to base paint. VOC level may increase significantly depending on the colorant choice.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

SURFACE PREPARATION

Wood:

Sand to a fresh surface. Patch imperfections with wood filler. Heavily stained areas, including tannin stains on wood, may require an appropriate stain-blocking primer.

Masonry:

All new surfaces must be cured according to the supplier's recommendations — usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface.

Metal:

New galvanized surfaces should be allowed to age 6 months before painting. Wash to remove any oil, grease or other surface contamination using a water-based cleaner-degreaser. Do not use hydrocarbon solvents for cleaning. Remove all corrosion with sandpaper, steel wool or other abrading method. All bare metal surfaces should be primed with a rust-inhibitive metal primer.

Clean Mildew from the Surface:

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

Note:

If using over stained areas, allow to dry 4 hours, apply test area with preferred topcoat. If bleeding occurs use Valspar® Stain Stopper, Valspar® Bonding Primer or other appropriate stain-blocking primer.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARRANTY

SATISFACTION GUARANTEE – LIMITED

WARRANTY: If this product, when applied and maintained according to product application and maintenance instructions to a properly prepared surface, fails to perform to your complete satisfaction, manufacturer shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate or improper application or maintenance of the product. This is your sole remedy under this warranty. **THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. Valsparpaint.com/1-877-VALSPAR

CAUTIONS

CONTAINS CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

16 (1/10)

First Aid: Eye Contact: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

101 W. Prospect Ave. Cleveland, OH

888.313.5569

valsparpaint.com

Revised: 07/18/2023