



Valspar® Reserve® Interior Latex Flat Paint

GENERAL DESCRIPTION

Valspar® Reserve® paint is our most advanced protection in just one coat. Our ultra-rich, fade resistant color paired with outstanding resistance against scuffs, scrubs and stains so your color stays true longer.

PRODUCT FEATURES

- Our most advanced protection in just one coat
- Ultra rich, fade resistant color
- Remarkable hide and coverage
- Outstanding resistance against scuffs, scrubs and stains
- Provides a mildew-resistant finish
- 100% acrylic
- Lifetime limited warranty

RECOMMENDED USES

Properly prepared interior walls, trim and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

- Quart – 4 per carton
- Gallon – 4 per carton
- 5 Gallon pail

COMPOSITION

Base and Fill Levels
(oz./gal.)

Ultra White (2916562, 2916574, 2916584)	124
Tint Base B (2916560, 2916572)	120
Tint Base C (2916561, 2916573)	116

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull.

Drywall: Fill cracks and holes with patching paste and sand smooth.

Plaster, Masonry, Block: New surfaces must cure at least 30 days. Fill rough surfaces if desired.

Wood: Sand to a fresh surface. Patch imperfections with wood filler.

Priming: This paint can be used to prime patched areas and bare surfaces before applying the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, prime with an appropriate tintable primer for optimal color accuracy and coverage.

Clean Mildew from the Surface: Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray. Thinning not required. Paint the ceiling first, then walls and trim. For roller application, cover approximately a 2' x 2' area using an "N" pattern. Finish with light roller strokes in one direction. Certain deep or bright colors may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

Airless Spray:

Pressure: 2000 PSI

Tip: 0.015–0.019"

Brush: Premium-quality polyester

Roller: Premium-quality roller 3/8" nap

PRODUCT SPECIFICATIONS

Vehicle Type: 100% Acrylic

VOC (g/L): < 50 g/L as per 40 CFR 59.406

Flashpoint: 499°F

Viscosity: 95 – 101 Krebs Units

Volume Solids: 43 ± 2%

Weight Solids: 57 ± 2%

Weight Per Gallon: 11.07lb

Gloss: 0-6 Units @ 85°

Coverage: Up to 400 sq. ft./gallon

Recommended Film Thickness:

4 mils Wet

1.5 mils Dry

Dry Time: @ 77 °F and 50% Relative Humidity

To The Touch: 1 hour

Recoat: 2-4 hours

Application Temperature: 50-90°F

CERTIFICATION

GREENGUARD Gold Approved

REGULATORY COMPLIANCE

Current as of: 2/1/2021

OTC

OTC Phase II

SCAQMD

CARB

CARB SCM 2007

Canada

LEED® v4 & v4.1 Emissions

LEED® v4 & v4.1 V.O.C. EPD-

NSF® Certified

MIR-Product Lens Certified MPI®

CLEANUP/DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.



LEAD WARNING

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

LIFETIME LIMITED WARRANTY

If this product, when applied according to product application instructions to a properly prepared interior surface, fails to perform to your complete satisfaction for as long as you own your home, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the product. This is your sole remedy under this warranty. This warranty is made to the original residential consumer paint purchaser and is not transferable. THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. Valsparpaint.com / 1-877-VALSPAR.

CAUTIONS

CONTAINS CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.** 16 (1/10)

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.
**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

Cleveland, OH
valsparpaint.com
888.313.5569
Revised: 5/8/2023
VALRESERVEFLT