

### GENERAL DESCRIPTION

Valspar Zone Marking Latex Paint is a quality, long-lasting paint for traffic or zone marking. The safe, easy-to-use formula has very low odor and dries quickly without discoloration from asphalt bleeding. It is ideal for marking parking lots and safety zones, and improving curb appeal.

### PRODUCT FEATURES

- Long-term performance
- Produces crisp, clean lines
- Fast drying
- High-visibility colors
- Easy to apply
- Passes Fed. Spec TT-P-1952B

### RECOMMENDED USES

Use on interior and exterior cured asphalt, cured concrete, pavers, brick or masonry, such as parking lots, curbs, playgrounds, warehouses, etc.

### COMPOSITION

#### Fill Levels

White (00135) - 1 Gallon	128 (oz./gal.)
White (00135) - 5 Gallon	640 (oz./gal.)
Yellow (00136) - 1 Gallon	128 (oz./gal.)
Yellow (00136) - 5 Gallon	640 (oz./gal.)
Blue (00137) - 1 Quart	32 (oz./gal.)
Blue (00137) - 1 Gallon	128 (oz./gal.)
Blue (00137) - 5 Gallon	640 (oz./gal.)
Red (00138) - 1 Gallon	128 (oz./gal.)
Red (00138) - 5 Gallon	640 (oz./gal.)

### REGULATORY COMPLIANCE

Current as of: 1/1/2023

SCAQMD	No
CARB	Yes
OTC	Yes
LADCO	Yes
EPA	Yes
Colorado AIM	Yes

### SURFACE PREPARATION

**General:** Take meticulous care to clean off dirt, grease, oil or other contaminants. If necessary, use TSP (or substitute) solution or commercial degreasing products to remove all oil and grease stains from surface. Remove loose and peeling paint. **New Asphalt:** Cure a minimum of 48 hours. Asphalt sealers must age 7 days before using Zone Marking Paint. **New Concrete:** Cure at least 30 days before painting. **Old unpainted concrete/asphalt:** Clean unpainted surfaces thoroughly, following the general instructions above. Ensure concrete surface feels like 120-grit sandpaper before application. **Painted or stained concrete/asphalt:** Remove all loose or peeling stain and paint. Dull glossy paint. Clean surface per general instructions. **Wet Surface Note:** On inclined surfaces, stairs and large painted areas subjected to pedestrian foot traffic, add an anti-slip agent at a level of 1 pound per gallon.

### LEAD WARNING

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### APPLICATION

Mix well before and during use. To ensure uniform color, intermix all cans of the same color. **Brush:** Use a quality polyester brush. **Roller:** Use a quality polyester roller with 3/8 to 1/2 inch nap. **Striping machine:** Use with all types of line striping equipment. **Glass beads:** Glass beads may be applied immediately to wet paint to create reflectorized marking. Use gravity flow equipment to dispense or hand broadcast glass beads at a rate of 1.5 lbs. per quart of paint.

### CLEANUP STORAGE AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic  
**Pigment Type:** Titanium Dioxide  
**Viscosity:** 88 - 105 Krebs Units  
**Flashpoint:** 66 - 96 °C  
**Sheen:** Flat  
**VOC (g/L):** less than 100 g/L  
**Volume Solids:** 42.69% - 61.19%  
**Weight Solids:** 55.04% - 75.52%  
**Weight Per Gallon:** 10.55 - 13.14 lbs./gal.  
**Practical Coverage:** Covers approximately 100 sq. ft. per gallon depending on surface porosity.  
**Recommended Film Thickness:** 15 mils wet  
**Line Width:** 4 inches  
**Linear Feet Per Gallon:** 300 feet  
**Dry Time @ 75 °F and 50% Relative Humidity**  
**To the Touch:** 15 - 30 minutes  
**Ready for Traffic:** 2 hours  
**Application Temperature:** 50–90 °F (10–32 °C)  
 Do not apply before rain.

### LIMITED WARRANTY

This warranty is made to you, the product purchaser who owns the property where the product is applied. This warranty is not transferable, except that if a contractor purchased and applied the product to the property, then the warranty is transferable to you. This warranty is only valid when the product is applied and maintained according to product application and maintenance instructions to a properly prepared surface. If the product fails to perform in accordance with applicable product literature, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect, damage or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application of the product. Your exclusive remedy and the sole liability of Valspar under this warranty, is the replacement of product or refund, and does not include labor or costs associated with the application or removal of any product. **IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.** Some states do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights and you may have other rights that vary from state to state.



## **CAUTIONS**

WARNING! Contains Ethylene Glycol and Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** Harmful if swallowed. May cause eye, skin, nose and throat irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention. **\*If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention. **\*If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.\* \*Call poison control center, hospital emergency room or physician immediately.

UCL13.1

Valspar, Cleveland, Ohio 44115  
Product Information Hotline: 877.825.7727  
valspar.com  
Revised: 1.1.2023