

### GENERAL DESCRIPTION

Valspar Elastomeric Masonry & Stucco Paint forms a weatherproof barrier against nature's harsh extremes. Stucco and masonry structures expand and contract in response to the weather and structural stresses. Unlike typical exterior house paints, this coating fills and bridges hairline cracks, helping to prevent damaging water penetration. It passes Federal Specification TT-C-555B, sec. 3.3.3, withstanding 98 mph wind-driven rain. This premium quality acrylic coating protects your home like a flexible blanket...keeping your masonry and stucco safe and beautiful for years to come. It is available in white and can be tinted to many custom colors to make your home a showplace!

### PRODUCT FEATURES

- Flexible-elastic finish
- Seals out weather and water
- Withstands 98 mph wind-driven rain
- Bridges hairline cracks
- 100% acrylic high-build formula

### RECOMMENDED USES

Use on properly prepared, exterior-masonry surfaces including cement, cinder block, stucco, concrete and brick. Do not use on glazed brick, floors or steps.

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material. Protect from freezing.

**Packaging:**

- Gallon – 4 per carton
- 5 gallon pail

### COMPOSITION

	Base and Fill Levels (oz./gal.)
White (2930)	126
Medium Base (2932)	124

### APPLICATION AND CLEANUP

Paint only when air or surface temperatures are between 35–90 °F (2–32 °C). Use a paint paddle to stir paint up from the bottom of the can. Intermix containers of the same color. Apply this product heavily to achieve the best weatherproofing characteristics. Cover grass and shrubbery with plastic or cloth. Apply two coats of this product to ensure that the correct film thickness (10 mil dry film) is achieved. The recommended spreading rate on a smooth surface is 130 sq.ft. per gallon per coat (a 10' x 13' area). On rough stucco or other uneven surfaces, this may be as low as 90 sq.ft. per gallon per coat. NOTE: For the two coats, you will need one gallon for every 45–65 sq.ft. (4.2–6 m<sup>2</sup>). Clean up with warm, soapy water.

**Roller (Preferred):**

Premium-quality 1" to 1-1/4" nap synthetic roller cover. Always roll with a fully loaded wet roller – never dry roll. Do not stretch this coating. Be sure all low spots and gaps are covered. It is normal for painted surfaces to show roller marks.

**Airless Spray:**

Apply with a 1–2 gallon-per-minute capacity pump at 2500 PSI minimum with a 0.025" tip. Adjust pressures to suit your needs. Always follow spray application by back-rolling with a wet applicator. This will ensure that the paint is worked into the surface. Thin with water for spray application (no more than 8 oz. per gallon), if needed. Do not allow the coating to dry in equipment or it will be more difficult to clean.

**Brush (not recommended):**

Use only for small touch-ups.

### SYSTEM

### RECOMMENDATIONS

**Masonry and Stucco:**

- Self-priming
- 2 Coats: Elastomeric Masonry and Stucco Paint

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic  
**Pigment Type:** Titanium Dioxide  
**Viscosity:** 104–110 Krebs Units  
**Sheen:** 0–6 Units @ 60° angle  
**Flashpoint:** N/A  
**VOC:** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406  
**Volume Solids:** 44%  
**Weight Solids:** 56%  
**Weight Per Gallon:** 10.81 lbs./gal.  
**Practical Coverage:** Covers 90–130 sq. ft. per gallon (9.3–23 m<sup>2</sup> per 3.78 L) depending on surface porosity. Two coats required for optimal coverage.  
**Recommended Film Thickness:**  
 24 mil Wet      10 mil Dry  
**Dry Time @ 77 °F and 50% Relative Humidity**  
**To The Touch:** 1–2 hours  
**Recoat:** 24 hours  
**Application Temperature:** 35–90 °F (2–32 °C)  
**Elasticity:** 400%  
**Tensile Strength:** 400 psi

### CERTIFICATIONS

Current as of: 8/7/2017

MPI #	N/A
MPI GPS 1	N/A
MPI GPS 2	N/A
LEED (US)	Yes
LEED (Canada)	Yes

### REGULATORY COMPLIANCE

Current as of: 8/7/2017

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

### STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

### SURFACE PREPARATION

#### **General:**

Read the Lead Warning paragraph. Apply paint to clean, sound surfaces. Large cracks, crumbling areas or water damage may need professional repair. New concrete or stucco must cure a month before applying a finish.

#### **Cleaning the Surface:**

Old or existing surfaces; remove dirt, grease, mildew, algae, efflorescence and loose, peeling coating. Pressure washer and masonry and stucco cleaner will ensure a clean, chalk and dirt free surface. Follow all label instructions and rinse well. Caution: Improper power washer use may cause damage to stucco.

#### **Facts About Efflorescence:**

Efflorescence is a white crusty material which migrates to the surface of masonry over time. It is caused by water entry within the wall itself. If present, find the source of water entry (cracked parapet cap tiles, open joints or cracks, etc.) and repair before painting. To remove, use a power washer, wire brush or scrape. Stubborn efflorescence can be removed with a mild muriatic acid solution. Protect eyes and skin by wearing rubber gloves and eye goggles.

#### **Clean mildew from the surface:**

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

#### **Filling in Cracks and Patching:**

Hairline cracks (1/16" or less) can be covered with this product. Cracks larger than 1/16" must be cleaned to remove all loose stucco or masonry. For stucco, fill gaps with exterior stucco texture finish, following label instructions. For masonry gaps, fill with concrete patch. Note: Large areas of crumbling masonry indicate a serious problem; consult a professional contractor.

#### **Caulking:**

Caulk all joints, seams and cracks around windows, doors and trim to eliminate sources of moisture entry.

### SURFACE PREP. CONTINUED

#### **Priming:**

Priming is not required on masonry surfaces in sound or good condition (cured, no efflorescence, etc.). For new masonry and stucco, mildly chalking surface, or surfaces in poor condition, prime with Valspar® Masonry and Stucco Sealer and Conditioner or Valspar Exterior Latex Primer. If overall surface is in good condition, spot prime as needed. Coarse textured surfaces require block filler.

### LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### LIMITED WARRANTY

This product is warranted to meet the application, appearance and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

### CAUTIONS

WARNING! Contains Ethylene Glycol and Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** Harmful if swallowed. May cause eye, skin, nose and throat irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. DO NOT TAKE INTERNALLY. Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. WARNING: This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

UCL 13.1

**For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631  
877.825.7727  
valsparpaint.com  
Revised: 8/7/17  
Version: 2930B