



Valspar® Fast Prep

No. 82096 Series

GENERAL DESCRIPTION

Fast Prep All-in-One Concrete Cleaner is the crucial first step in most Valspar concrete-coating projects to ensure the best finish. Fast Prep extends the life of the coating, provides maximum durability and allows the coating to bond tightly to your concrete. Fast Prep cleans, degreases and etches in one easy step, saving you time and money.

PRODUCT FEATURES

- Cleans, degreases and etches in one easy step
- Ensures maximum coating adhesion and durability
- Helps prevent peeling
- Safer and easier to use than muriatic acid

REGULATORY COMPLIANCE

Current as of: 5/15/2014

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. **Read directions and cautions thoroughly before using this product. For use on concrete only.** This product prepares concrete for maximum durability and adhesion. Use Fast Prep™ to clean and etch concrete prior to painting or sealing. Surface must be free of loose dirt, dust, leaves, dried paint or other debris. Use a stiff bristle broom to sweep floor. Clean out cracks and corners where dirt and other debris may be embedded or hard to reach. Tip: Use a leaf blower after sweeping to blow away any excess dust or dirt off surface. Wet the surface down completely with a garden hose.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION AND CLEANUP

Wear rubber boots, rubber gloves and eye protection at all times while using this product. Protect plants and landscaping from direct contact and runoff. Transfer into a plastic watering can. Do not use a metal watering can. Inspect floor for grease and oil stains. Spot apply Fast Prep™ directly to these areas and scrub thoroughly with a stiff brush. Rinse with water. Difficult areas may require a second application and scrubbing. Divide the surface into 10' x 10' sections. Pre-wet surface using a garden hose, avoid puddles. To apply Fast Prep, sweep watering can back and forth as you pour to ensure complete coverage. Using a stiff bristle brush, spread Fast Prep over section completely. It should begin to fizz or bubble, this is normal. Rinse all tools, material and personal protection with water before storing. Wash affected clothing.

Note: If Fast Prep is not fizzing, it is not working. The concrete may have been previously sealed, preventing the Fast Prep from working. The sealers must be totally removed before reapplying Fast Prep. Use the brush to scrub the solution into the surface in 2 directions, perpendicular to each other. Brush thoroughly in short, firm motions over stains and spots. When finished with one section, spray with water and wash away residue. Pre-wet the next 10' x 10' (3 m x 3 m) section and repeat steps. When finished, re-rinse completely with garden hose, washing away loosened material and cleaner residue. Keep rinsing until water runs clean. All loosened powders must be removed or they will interfere with coating adhesion. Allow surface to dry completely, at least 4 hours or overnight, before applying any coating.

STORAGE AND DISPOSAL

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, rinse with large amounts of clean water. Dispose of container and/or unused contents in accordance with local, state and federal regulations.

LIMITED WARRANTY

This product is warranted to be free of defects and to be of merchantable quality. If you are not satisfied, return to the place of purchase with the unused portion and the original sales receipt. If the product is found to be defective, you will receive a replacement of the defective product or, at our option, a full refund. This limited warranty is your only warranty and excludes labor costs or any other incidental or consequential damages. Application of any replacement product is your responsibility. This warranty gives you specific legal rights and you may have other legal rights which vary from state to state.

PRODUCT SPECIFICATIONS

VOC (g/L): less than 4%

Weight Per Gallon: 8.77 lbs./gal.

Practical Coverage: Ready to use on garage floors. One gallon of Fast Prep™ (as supplied) covers about 250 sq. ft. (1 car garage). For other areas such as patios, driveways, sidewalks, etc., mix Fast Prep into 1 gallon of water and stir for 1 minute. This 2-gallon mixture will cover 500 sq. ft.

Application Temperature: 50–90 °F (10–32 °C)

CAUTIONS

WARNING! VAPOR HARMFUL. CAUSES SEVERE EYE IRRITATION.

WARNING! CONTAINS ORGANIC ACID SALT AND GLYCOL ETHERS. KEEP OUT OF THE REACH OF CHILDREN. VAPOR HARMFUL. May affect the brain or nervous system causing dizziness, headache or nausea. Causes severe eye irritation. Causes skin, nose and throat irritation. May be harmful if absorbed through the skin. Harmful if swallowed. **USE ONLY WITH ADEQUATE VENTILATION.** Avoid breathing vapors. If using indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. **FIRST AID: EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.* **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **IF SWALLOWED:** Do not induce vomiting. Get medical attention immediately.*

* Call poison control center, hospital emergency room or physician immediately.

CL 1.3 DPM

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

8725 W. Higgins Rd., Chicago, IL 60631

877.825.7727

valsparpaint.com

Revised: 5/15/14

Version: 82096A