

### GENERAL DESCRIPTION

Valspar Natural Look, Low-Gloss Protective Sealer forms a long-lasting, protective barrier on concrete, brick, masonry, natural stone and pavers. The low-gloss formula protects against weather, household chemicals, scuffs & peeling.

### PRODUCT FEATURES

- Low-gloss finish protects without altering appearance
- Excellent for pavers; also great on concrete, brick and tile
- Locks out weather, household chemicals, scuffs and peeling
- Easy to apply; soap and water cleanup
- Use over semi-transparent stain or bare concrete & masonry

### RECOMMENDED USES

Use on interior and exterior bare concrete, masonry, mortar, brick, slate, flagstone & pavers. Can be used over semi-transparent stains.

### COMPOSITION

<b>Clear</b>	<b>Base and Fill Levels</b>
	128 (oz./gal.)

### REGULATORY COMPLIANCE

Current as of: 1/1/2023	
SCAQMD	No
CARB	Yes
OTC	Yes
LADCO	Yes
EPA	Yes
Colorado AIM	Yes

### CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room or physician immediately. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

### SURFACE PREPARATION

**General:** All surfaces must be clean, dry and free of all loose, peeling paint or contaminants

**Bare concrete:** Allow 60 days minimum for new concrete to cure before sealing.

**Previously sealed surfaces:** Clean with an all-purpose cleaner (TSP or substitute). Previously sealed surfaces must be porous and able to accept additional sealer

**Test surface porosity before sealing:** Avoid using this product on nonporous, sealed surfaces. To test, place a few drops of water on the surface. If water sinks in, the surface is porous enough to use this finish. If water remains on the surface, do not use.

### LEAD WARNING

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### APPLICATION

Use a roller or low-pressure, garden-type sprayer. While the first coat is still wet, apply a second coat to maximize protection. Allow 5-10 minutes for final penetration, then use a clean, dry cloth to wipe off all excess that did not soak into the surface. **Do not pond or puddle this product.**

### CLEANUP, STORAGE AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Silicone emulsion

**Viscosity:** 8–13 Ford Cup

**VOC (g/L):** less than 100 g/L

**Volume Solids:** 3%

**Weight Solids:** 3%

**Practical Coverage:** Covers approximately 75–150 sq. ft. (7–14 m<sup>2</sup>) per gallon, depending upon surface porosity. Do not thin.

**Dry Time @ 77 °F and 50% Relative Humidity**

**To the Touch:** 2 hours **Light Foot Traffic:** 24 hours

**Application Temperature:** 50–90 °F (10–32 °C)

### LIMITED WARRANTY

This warranty is made to you, the product purchaser who owns the property where the product is applied. This warranty is not transferable, except that if a contractor purchased and applied the product to the property, then the warranty is transferable to you. This warranty is only valid when the product is applied and maintained according to product application and maintenance instructions to a properly prepared surface. If the product fails to perform in accordance with applicable product literature, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect, damage or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application of the product. Your exclusive remedy and the sole liability of Valspar under this warranty, is the replacement of product or refund, and does not include labor or costs associated with the application or removal of any product. **IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.** Some states do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights and you may have other rights that vary from state to state.

Valspar, Cleveland, Ohio 44115  
 Product Information Hotline: 877.825.7727  
[valspar.com](http://valspar.com)  
 Revised: 1.1.2023