



Valspar® Interior/Exterior Concrete Bonding Primer

No. 82000

GENERAL DESCRIPTION

Valspar® Concrete Bonding Primer penetrates and bonds to etched concrete, enhancing the adhesion of the top coat finish. Ideal for use under Valspar® Latex Porch & Floor Paint, Valspar Solid Color Concrete Stain and any other acrylic and epoxy paint.

PRODUCT FEATURES

- Maximum adhesion to concrete for a flawless top coat
- Ensures resistance to peeling and flaking
- Goes on white to ensure complete coverage during application
- Shortens project time; can be recoated in one hour

RECOMMENDED USES

For interior or exterior properly prepared concrete, wood or primed metal.

SURFACE PREPARATION

General:

All surfaces must be clean, dry and free of all loose, peeling paint or contaminants. Areas where

ponding water is evident should be leveled prior to application.

Bare concrete:

Allow 60 days minimum for new concrete to cure before painting. Clean and etch new or bare concrete with Valspar® Fast Prep® Cleaner, Degreaser & Etcher. Follow all Fast Prep label instructions.

Previously painted surfaces:

Clean with an all-purpose cleaner (TSP or substitute) and remove gloss from shiny surfaces by sanding or using a chemical deglosser.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION AND CLEANUP

Mix well before and during use. Use a premium-quality, polyester brush for small area (stairs, etc.). For large areas, pour coating in a long, continuous bead across the "shorter side" of the surface. Spread the product uniformly with a premium-quality, 1/4" or 3/8" nap roller and finish with long, even strokes in one direction. Product goes on white for complete coverage then dries clear.

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

LIMITED WARRANTY

This warranty is made to you, the product purchaser who owns the property where the product is applied. This warranty is not transferable, except that if a contractor purchased and applied the product to the property, then the warranty is transferable to you. This warranty is only valid when the product is applied and maintained according to product application and maintenance instructions to a properly prepared surface. If the product fails to perform in accordance with applicable product literature, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect, damage or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application of the product. Your exclusive remedy and the sole liability of Valspar under this warranty, is the replacement of product or refund, and does not include labor or costs associated with the application or removal of any product. IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY. Some states do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights and you may have other rights that vary from state to state.

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic
Viscosity: 70–80 Krebs Units
Flashpoint: 205 °F
VOC (g/L): less than 100 g/L
Volume Solids: 21%
Weight Solids: 23%
Weight Per Gallon: 8.54 lbs./gal.
Practical Coverage: Covers approximately 250 sq. ft. (23 m²) per gallon. Do not thin.
Recommended Film Thickness:
6.4 mil Wet 1.3 mil Dry
Dry Time @ 77 °F and 50% Relative Humidity
Dries tacky, ready for top coating in 1 hour. Do not wait more than 4 hours to apply top coat or re-priming may be necessary.
Application Temperature: 50–90 °F (10–32 °C)
Storage Temperature: 40–90 °F (5–32 °C)

REGULATORY COMPLIANCE

Current as of: 1/1/2023	
SCAQMD	No
CARB	Yes
OTC	Yes
LADCO	Yes
EPA	Yes
Colorado AIM	Yes

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.
15 (1/10)

Valspar, Cleveland, Ohio 44115
Product Information Hotline: 877.825.7727
Valspar.com
Revised: 1.1.2023