



# Valspar® Anti-Skid Porch and Floor Paint

## No. 82030 Series

### GENERAL DESCRIPTION

Valspar® Anti-Skid Porch and Floor Paint is a 100% acrylic, texturized-surface coating for concrete, asphalt and other floor surfaces: walkways, tennis courts, pool decks, steps, ramps, laundry areas, etc. Valspar Anti-Skid floor paint provides excellent traction quality and color fastness for interior and exterior applications. Easy to apply, soap and water cleanup.

### PRODUCT FEATURES

- Interior/Exterior
- Ideal for steps, walkways & pool decks
- Skid resistant coating
- Fast drying

### RECOMMENDED USES

- Concrete
- Asphalt
- Previously coated surfaces
- Primed wood and metal

#### Not for use:

- Ponding water areas
- Garage floors or parking areas

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material. Protect from freezing.

#### Packaging:

Gallon – 4 per carton

**Case Weight:** 51.8 lbs.

### COMPOSITION

#### Base and Fill Levels

	(oz./gal.)
<b>Light Gray</b> (82030)	128
<b>Dark Gray</b> (82031)	128
<b>Base 2</b> (82032)	126
<b>Base 4</b> (82033)	116

### APPLICATION AND CLEANUP

Mix well before and during use. If using more than one container, intermix all cans of the same color. Use a premium-quality, polyester brush for small area (stairs, etc.). For large areas, pour Valspar® Anti-Skid Porch and Floor Paint coating in a long, continuous bead across the "shorter side" of the surface. Spread the product uniformly with a premium-quality, 1/4" or 3/8" nap roller and finish with long, even strokes in one direction. After drying 24 hours, apply the second coat if necessary or desired, at a right angle to the first coat — again finishing with long, even strokes in one direction. Clean tools and hands with warm, soapy water. Discard used roller covers. Do not allow water to pond or puddle on newly painted surfaces.

### SYSTEM

#### RECOMMENDATIONS

##### Concrete and Masonry:

- 1 Coat: Valspar® Exterior Latex Primer
- 1-2 Coats: Anti-Skid Porch and Floor Paint

##### Bare Wood:

- 1 Coat: Valspar® Exterior Oil or Latex Primer
- 1-2 Coats: Anti-Skid Porch and Floor Paint

##### Previously Coated Surfaces:

- 1 Coat: Valspar® Exterior Oil or Latex Primer
- 1-2 Coats: Anti-Skid Porch and Floor Paint

##### Metal:

- 1 Coat: Valspar® Armor Anti-Rust Primer
- 1-2 Coats: Anti-Skid Porch and Floor Paint

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic resin

**Viscosity:** 108–118 Krebs Units

**Flashpoint:** N/A

**VOC (g/L):** less than 50 g/L 0.42 lb/gal as per 40 CFR 59.406

**VOC (lbs./gal.):** 0.32

**Volume Solids:** 41%

**Weight Solids:** 60%

**Weight Per Gallon:** 12.1 lbs./gal.

#### Practical Coverage:

The first coat covers approximately 75 sq<sup>2</sup> (7 m<sup>2</sup>) per gallon. The second coat covers about 100 sq<sup>2</sup> (9.3 m<sup>2</sup>) per gallon. Thinning is not recommended.

#### Recommended Film Thickness:

18.0 mil Wet      7.4 mil Dry

#### Dry Time @ 77 °F and 50% Relative Humidity

**Recoat:** 24 hours

**Light Foot Traffic:** 24 hours

**Normal Use:** 48 hours for normal use

**Washing:** Allow at least 7 days before washing. Use mild detergent and sponge.

**Application Temperature:** 50–90 °F (10–32 °C)

### REGULATORY COMPLIANCE

Current as of: 9/12/2017

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

### STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.



# Valspar® Anti-Skid Porch and Floor Paint

## No. 82030 Series

### SURFACE PREPARATION

#### **General:**

Read the Lead Warning paragraph. The surface must be clean, dry and free of all loose or peeling paint. Thoroughly clean surface and remove wax and grease with an all-purpose cleaner (TSP or substitute). Clean joints and cracks to remove all foreign material. Patch voids with appropriate crack patching material. Areas where ponding water is evident should be leveled prior to application. Although not required, a coat of Concrete Primer prior to application of Anti-Skid Porch and Floor Paint coats will increase the adhesion to these properly prepared surfaces.

#### **Concrete:**

New concrete, masonry surfaces and mortar should be cured 60 days. Remove all form release or curing agents. New, unpainted or smooth-worn concrete must be etched with a concrete cleaner, degreaser and etcher for proper penetration and adhesion. Follow all label instructions. Remove all loose material or dust. Soft concrete or masonry surfaces should be primed with a Valspar® Exterior Latex Primer.

#### **Etching:**

New, unpainted or smooth-worn concrete must be etched with a muriatic acid solution for proper penetration and adhesion. Before preparing acid solution, READ ALL CAUTIONS AND WARNINGS on acid packaging. Wear appropriate protective clothing, goggles and rubber gloves when handling acid. Mix 1 quart of muriatic acid and 1 gallon of water. Flush floor with acid solution. DO NOT BREATHE VAPORS and make certain there is good ventilation. After 30 minutes, or when acid solution stops bubbling, rinse with water while scrubbing the floor with a stiff broom to remove all powdery residue. Allow to dry. Properly etched concrete will feel like rough sandpaper.

#### **Asphalt:**

New asphalt should be weathered 4 to 6 months prior to application. Do not apply over shiny asphalt or freshly applied tar emulsion driveway sealers.

#### **Bare Wood:**

Remove sap from knots and sappy areas. Spot prime then prime entire area with appropriate Valspar® Exterior Latex or Oil-Based Primer.

### SURFACE PREP CONTINUED

#### **Metal:**

Hand or power tool clean steel to remove loose mill scale and rust. Remove oily residues and contaminants with solvent or appropriate cleaning solution. Change rags often, to assure that residual contaminants are completely removed. Prime with Valspar® Armor Anti-Rust Primer.

### LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### LIMITED WARRANTY

This product is warranted to perform to your satisfaction at the time of application when applied to a properly prepared residential surface in accordance with the label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

### CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. USE ONLY WITH ADEQUATE VENTILATION. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use. DO NOT TAKE INTERNALLY. Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist. WARNING: This product contains a chemical known to the State of California to cause cancer. FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.\* IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* IF SWALLOWED: Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

CL 3.3

**For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631  
877.825.7727  
valsparpaint.com  
Revised: 9/12/17  
Version: 82030B