

GENERAL DESCRIPTION

Valspar Solid Color Concrete Stain is fortified with new, heavy-duty resin technology to provide maximum protection to concrete and masonry surfaces. It forms a low gloss, durable finish that protects against hot tire pickup, flaking and peeling. Use on properly prepared exterior concrete surfaces such as pool decks, patios, sidewalks, driveways and privacy walls. **Note:** Do not apply this product over surfaces that have been treated with water repellent sealers or to damp or wet concrete! Not recommended for garage floors.

PRODUCT FEATURES

- Renew patios, driveways, and sidewalks
- Transforms old concrete for added curb appeal
- Protects from sun, water, and household chemical damage

RECOMMENDED USES

- Patios
- Driveways
- Pool decks
- Masonry surfaces

Not for use:

- Asphalt

COMPOSITION

Base and Fill Levels (oz./gal.)

Concrete Gray	128
Base 2 (1082322)	124
Base 4 (1082324)	116

STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

REGULATORY COMPLIANCE

Current as of: 11/10/2016

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

SURFACE PREPARATION

General: Read the Lead Warning paragraph. The surface must be clean, dry and free of all loose or peeling paint or contaminants. Patch voids with appropriate crack patching material. Areas where ponding water is evident should be leveled prior to application.

Bare concrete: Allow 60 days minimum for new concrete to cure before sealing. Clean and etch new or bare concrete with Valspar® Fast Prep® Cleaner, Degreaser & Etcher. **Follow all Fast Prep label instructions.**

Previously painted/Stained concrete: Strip off all old coating and then follow bare concrete instructions.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION AND CLEANUP

Mix well before and during use. Intermix cans of the same color. Apply with a high-quality, polyester brush or 1/4" or 3/8" nap roller. Spread product evenly and finish with long, even strokes in the same direction. Two coats are recommended for most applications (wait 24 hours for second coat). Clean up with warm, soapy water.

LIMITED WARRANTY

This product is warranted to be free of defects and to be of merchantable quality. If you are not satisfied, return to the place of purchase with the unused portion and the original sales receipt. If the product is found to be defective, you will receive a replacement of the defective product or, at our option, a full refund. This limited warranty is your only warranty and excludes labor costs or any other incidental or consequential damages. Application of any replacement product is your responsibility. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic resin

Viscosity: 90–110 Krebs Units

Flashpoint: N/A

VOC (g/L): less than 100 g/L

Volume Solids: 24%

Weight Solids: 36%

Weight Per Gallon: 9.8 lbs./gal.

Practical Coverage: One gallon covers approximately 200 sq. ft. (18 m²) over coarse, textured surfaces and 400–500 sq. ft. (37–46 m²) over smooth surfaces. Do not thin.

Dry Time @ 77 °F and 50% Relative Humidity

To the touch: 2 hours

Light foot traffic: 24 hours

Normal Use: 72 hours

Application Temperature: 50–90 °F (10–32 °C)

CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. DO NOT TAKE INTERNALLY. Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. WARNING: This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.* *Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732

8725 W. Higgins Rd., Chicago, IL 60631
888.313.5569
valsparpaint.com
Revised: 11/10/16