



# Valspar® Semi-Transparent Concrete Stain

## No. 82062 Series

### GENERAL DESCRIPTION

Transform your outdoor space into a beautiful retreat with Valspar Semi-Transparent Concrete Stain. Highly versatile and easy to apply, the stain lets you achieve a natural look with one color, or take it to the next level with multiple colors or patterns. Durable formula provides long-lasting decorative color while protecting from weather and household-chemical damage. Semi-Transparent Concrete Stain imparts a low gloss; for added protection and a rich, glossy finish, apply Valspar® Wet Look High Gloss Sealer.

### PRODUCT FEATURES

- Natural-stone look for patios, driveways and sidewalks
- Protects from sun, water and household-chemical damage
- Apply one color, or create a custom look with multiple colors
- For interior and exterior use

### RECOMMENDED USES

- Patios
- Pool decks
- Sidewalks
- Driveways
- Do not use on garage floors

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material. Protect from freezing.

**Packaging:**

Gallon – 4 per carton  
5 gallon

### COMPOSITION

**Base and Fill Levels**

(oz./gal.)

Tint Base (Gallon)	124
Tint Base (5 Gallon Pail)	620

### APPLICATION AND CLEANUP

Avoid application in direct sunlight or onto hot concrete surfaces. Mix well before and during use. Intermix cans of the same color. Dampen concrete thoroughly with water; remove any standing water or puddles. Use a pump sprayer set to a fine-spray pattern. Apply stain to small sections (4' x 4') at a time, spraying in a random circular pattern. Work quickly to maintain a wet edge. For a more uniform appearance, immediately back-roll wet areas with a 3/8" nap roller. Do not let stain "puddle" on surface. Allow to dry 4 hours before deciding if another coat is needed. A second coat will yield a darker, more uniform color. TIP: For a more varied appearance, choose a 2-color effect. Spray a second color onto the first wet coat of stain in a random pattern, but do not back-roll. Clean up with warm, soapy water.

Use VALSPAR® 82390, Wet Look High Gloss Sealer to provide maximum protection from household chemicals and wear in high-traffic areas.

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic resin

**Viscosity:** 15–25 Zahn

**Flashpoint:** N/A

**VOC (g/L):** less than 100 g/L

**Volume Solids:** 18%

**Weight Solids:** 21%

**Weight Per Gallon:** 8.6 lbs./gal.

**Practical Coverage:** Covers approximately 200–400 sq. ft. per gallon (18–37 m<sup>2</sup> per 3.78 L) depending on surface porosity. Do not thin.

**Recommended Film Thickness:**

5.3 mil Wet      1.0 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To the Touch:** 2 hours

**Recoat:** 24 hours

**Light Use:** 24 hours

**Normal Use:** 72 hours

**Application Temperature:** 50–90 °F (10–32 °C)

### REGULATORY COMPLIANCE

Current as of: 10/3/2023

SCAQMD	No
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO / OTC II	Yes
US National	Yes

### STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.



# Valspar® Semi-Transparent Concrete Stain

---

## No. 82062 Series

### **SURFACE PREPARATION**

**General:** Read the Lead Warning paragraph. All surfaces must be clean, dry and free of all loose, peeling paint or contaminants. Do not apply over surface treated with water repellent sealers.

**Bare concrete:**

Allow 30 days minimum for new concrete to cure before painting. Clean and etch new or bare concrete with Fast Prep™ Cleaner, Degreaser & Etcher. Follow all Fast Prep label instructions.

**Previously painted/Stained concrete:**

Strip off all old coating and then follow bare concrete instructions.

### **LEAD WARNING**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **LIMITED WARRANTY**

This product is warranted to be free of defects and to be of merchantable quality. If you are not satisfied, return to the place of purchase with the unused portion and the original sales receipt. If the product is found to be defective, you will receive a replacement of the defective product or, at our option, a full refund. This limited warranty is your only warranty and excludes labor costs or any other incidental or consequential damages. Application of any replacement product is your responsibility. This warranty gives you specific legal rights and you may have other legal rights which vary from state to state.

### **CAUTIONS**

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. USE ONLY WITH ADEQUATE VENTILATION. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use. DO NOT TAKE INTERNALLY. Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist. WARNING: This product contains a chemical known to the State of California to cause cancer. FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.\* IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* IF SWALLOWED: Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

CL 3.3

**For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631  
877.825.7727  
valsparpaint.com  
Revised: 10/3/2023  
Version: 82062A