



# Valspar® Pristine™ Interior Latex Satin Paint

## No. 18540 – Series

### GENERAL DESCRIPTION

As one of our most advanced paint and primer products, Valspar® Pristine™ offers luxurious color, single-coat coverage, and an extra advantage: Clean Science™ Technology. Pristine was specifically engineered to repel dirt and resist stains, so it retains its smooth, clean finish over the years – even after repeated washing and scrubbing.

### PRODUCT FEATURES

- Ultra-smooth paint & primer
- Clean Science™ Technology – engineered to repel dirt and resist stains
- Luxurious, no-fade color
- Single-coat coverage
- Stay-clean smoothness
- Superior scrubability over time
- 100% acrylic latex
- Lifetime warranty

### RECOMMENDED USES

Properly prepared, interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement and metal

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material. Protect from freezing.

**Packaging:**

- Quart – 4 per carton
- Gallon – 4 per carton

### COMPOSITION

	Base and Fill Levels (oz./gal.)
White	128
Pastel Base (18548)	126
Tint Base (18542)	124
Clear Base (18545)	116

### APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, polyester brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction. Note: Some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage.

**Airless Spray:**

Pressure: 2000 PSI  
Tip: 0.017–0.019"

**Brush:** premium-quality nylon or polyester brush

**Roller:** premium quality synthetic, 3/8" nap

**Washing Instructions:** Wait at least 7 days before washing with a mild detergent and soft sponge.

### SYSTEM

#### RECOMMENDATIONS

**Plaster:**

Prime: Valspar Pristine Interior Latex Satin  
1–2 Coats: Valspar Pristine Interior Latex Satin

**Wood:**

Prime: Valspar Pristine Interior Latex Satin  
1–2 Coats: Valspar Pristine Interior Latex Satin

**Brick:**

Prime: Valspar Pristine Interior Latex Satin  
1–2 Coats: Valspar Pristine Interior Latex Satin

**Drywall:**

Prime: Valspar Pristine Interior Latex Satin  
1–2 Coats: Valspar Pristine Interior Latex Satin

**Cement:**

Prime: Valspar Pristine Interior Latex Satin  
1–2 Coats: Valspar Pristine Interior Latex Satin

**Metal:**

Prime: Metal primer  
1–2 Coats: Valspar Pristine Interior Latex Satin

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic resin

**Pigment Type:** Titanium Dioxide

**Viscosity:** 90–96 Krebs Units

**Sheen:** 35-45 Units @ 85° Angle

**Flashpoint:** N/A

**VOC:** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

**Volume Solids:** 39%

**Weight Solids:** 54%

**Weight Per Gallon:** 11.59 lbs./gal.

**Practical Coverage:** Covers up to 400 sq. ft. per gallon (37 m<sup>2</sup> per 3.78 L) depending on surface porosity. Do not thin.

**Recommended Film Thickness:**

4.0 mil Wet      1.6 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**  
**To The Touch:** 30–60 minutes

**Recoat:** 2–4 hours

**Application Temperature:** 50–90 °F (10–32 °C)

### REGULATORY COMPLIANCE

Current as of: 8/7/2017

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

### CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal.



# Valspar® Pristine™ Interior Latex Satin Paint

## No. 18540 – Series

### **SURFACE PREPARATION**

#### **General:**

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Remove gloss from shiny surfaces. Valspar Pristine paint can be used to prime patched areas and bare surfaces before applying the finish coat. For best results on heavily stained areas, use a coat of stain-blocking primer.

#### **Plaster:**

Allow new plaster to fully cure and sand smooth. Remove all sanding dust. Spot prime before applying the finish coat.

#### **Wood:**

Sand wood smooth and patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Spot prime new or bare surfaces before applying the finish coat.

#### **Brick:**

Masonry surfaces and mortar should be fully cured, usually 30 days. Remove all loose material or dust.

#### **Drywall/Wallboard:**

Fill cracks, pits and voids with patching compound, let cure and sand smooth. Remove all sanding dust. Spot prime new or bare surfaces before applying the finish coat.

#### **Cement:**

New concrete, masonry surfaces and mortar should be cured, usually 30 days. Remove all form release or curing agents. Remove all loose material or dust. Spot prime soft concrete or masonry surfaces before applying the finish coat.

#### **Metal:**

Prime bare metal surfaces with an appropriate metal primer.

### **LEAD WARNING**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **LIMITED WARRANTY**

This product is warranted for your complete satisfaction for as long as you reside in your home. This warranty covers product that is applied to a properly prepared residential surface in accordance with label directions and excludes product failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

### **CAUTIONS**

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:**  
**1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631  
877.825.7727  
[valsparpaint.com](http://valsparpaint.com)  
Revised: 8/7/17  
Version: 18540B