



Valspar® Professional Interior Latex Dry Fall Flat

No. 275 Series

GENERAL DESCRIPTION

Valspar interior latex dry drop paint provides a high hiding, fast-drying flat white finish that increases light reflectance in large commercial buildings. Also available in flat black.

PRODUCT FEATURES

- Overspray dries as it falls; water-based formulation cleans up easily
- Formulated for professional use in residential, commercial, institutional, and industrial applications
- Flash rust resistant

RECOMMENDED USES

Properly prepared interior, commercial-ceiling surfaces of plaster, masonry, wallboard, metal and wood.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

5 gallon pail

COMPOSITION

	Base and Fill Levels (oz. /gal.)
High Hiding White (275)	128
High Hiding Black (276)	128

APPLICATION AND CLEANUP

Use a paint paddle or mixing blade to stir paint thoroughly, bringing pigments to the top of the can. To ensure uniform color, intermix all cans of the same color. Recommended application is with airless spray but product may be brushed or rolled as needed. Under normal conditions (77°F and 50% Relative Humidity) overspray will dry to a harmless dust after a drop of 10 feet. Lower temperatures or higher humidity will require a longer drop distance. Coverage varies depending on the substrate and texture. Adjust fan width, atomization and gun distance from the surface to prevent curtaining while allowing maximum solvent release. Clean up with warm, soapy water.

Airless Spray:

Pressure: 2000 PSI

Tip: 0.013–0.017"

Thinning: Not recommended.

Tinting: Do not tint. Tinting this product will result in the loss of dry drop properties.

SYSTEM

RECOMMENDATIONS

Drywall/Wallboard (new):

1 Coat: Valspar® interior latex primer

1–2 Coats: Valspar Interior Latex Dry Fall Flat

Drywall (repaint):

1–2 Coats: Valspar Interior Latex Dry Fall Flat

Plaster:

1 Coat: Valspar® interior latex primer

1–2 Coats: Valspar Interior Latex Dry Fall Flat

Interior Wood & Composition Board:

1 Coat: Valspar® interior latex primer

1–2 Coats: Valspar Interior Latex Dry Fall Flat

Galvanized Metal:

1–2 Coats: Valspar Interior Latex Dry Fall Flat

Steel and Rusted Galvanized Metal:

1 Coat: Valspar® DTM Acrylic Primer

1–2 Coats: Valspar Interior Latex Dry Fall Flat

Interior Block, Concrete and Masonry:

1 Coat: Valspar® Latex Block Filler

1–2 Coats: Valspar Interior Latex Dry Fall Flat

PRODUCT SPECIFICATIONS

Vehicle Type: Vinyl Acrylic

Pigment Type: Titanium dioxide

Viscosity: 80–90 Krebs Units

Gloss: 0-10 @85° Flat

Flashpoint: N/A

VOC (g/L): < 50 g/L – 0.42 lbs. /gal as per 40 CFR 59.406

Volume Solids: 25 ± 2%

Weight Solids: 45 ± 2%

Weight Per Gallon: 11.30lbs./gal.

Practical Coverage: Covers up to 875 - 1350 sq. ft. per 5-gallon pail (116–162 m² per 18.9 L). Less on rough or porous surfaces.

Recommended Film Thickness:

6-9 mil Wet 1.5-2.3 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

To The Touch: 30 minutes

Recoat: 1 hour

Application Temperature: 60–110 °F (15–43 °C)

Storage Temperature: 40–110 °F (5–43 °C)

CERTIFICATIONS

Current as of: 3/19/2019

LEED (US) Yes

LEED (Canada) Yes

REGULATORY COMPLIANCE

Current as of: 3/19/2019

SCAQMD Yes

CARB 2000 SCM Yes

CARB 2007 SCM Yes

OTC/LADCO Yes

STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.



Valspar® Professional Interior Latex Dry Fall Flat

No. 275 Series

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. Clean the surface thoroughly to remove surface contamination, mildew, stains and rust with an appropriate cleaner. Scrape off any loose or peeling paint. Spot prime when needed. Remove gloss from shiny surfaces with light sanding. Prime with an appropriate Valspar® primer. All bare wood must be primed with a Valspar® latex primer or undercoater. For a smoother final appearance on wallboard, prime with a Valspar® interior latex primer.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

This product is warranted to meet the application, appearance and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state. CONTRACTOR AND COMMERCIAL CUSTOMERS: When used for commercial or nonresidential applications, this product is warranted to perform as indicated on the product label and to be free of material defects. At its option, Valspar® will replace or refund the original purchase price of this product if it does not perform as labeled or is proven to be defective. All other warranty terms above apply

CAUTIONS

WARNING! VAPOR HARMFUL.

WARNING! Contains Ethanol and Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with the eyes and skin. Wash thoroughly after use. Close container after each use. **DO NOT TAKE INTERNALLY.** NOTICE: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **First Aid: Eye Contact:** Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.* **If Inhaled:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Do not induce vomiting. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

CS 7.3s ET

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732

101 West Prospect Avenue
Cleveland, OH 44115
valsparpaint.com
Revised: 3/19/19
Doc Code: VALPRO275