

### PRODUCT DESCRIPTION

Valspar Professional Interior Latex Eggshell is professional grade paint with excellent touch-up, durability and great hide & coverage. It creates a washable film with excellent burnish resistance, providing a smooth, uniform finish that hides imperfections. Ideal for residential re-paint projects, remodeling and new home construction; this paint is formulated for spray, brush and roll application on properly prepared interior walls and ceilings.

### RECOMMENDED USES

Properly prepared interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement and metal.

Certifications/ Regulatory Compliance 8/8/2017			
MPI #	44	SCAQMD	Yes
GPS-1	Yes	CARB 2000 SCM	Yes
GPS-2	Yes	CARB 2007 SCM	Yes
LEED (US)	Yes	OTC/LADCO	Yes
LEED (Canada)	Yes	US National	Yes

### PRODUCT INFORMATION

BASE & FILL LEVELS**	SPECIFICATIONS
<p>High Hiding White (11800) 128 oz/gal                      Tintable White (11805) 126 oz/gal                      Light Base (11811) 124 oz/gal                      Medium Base (11812) 120 oz/gal                      Neutral Base (11814) 116 oz/gal</p> <p>**All bases available in gallon and 5-gallon sizes</p>	 <p><b>VEHICLE TYPE:</b> Vinyl copolymer  <b>PIGMENT TYPE:</b> Titanium Dioxide  <b>VISCOSITY:</b> 90–100 Krebs Units  <b>GLOSS:</b> 0–10 Units @ 60° angle  <b>SHEEN:</b> 12–22 Units @ 85° angle  <b>FLASHPOINT:</b> N/A  <b>VOC (g/L):</b> &lt; 50 g/L – 0.42 lb/gal as per 40 CFR 59.406  <b>VOLUME SOLIDS:</b> 33%  <b>WEIGHT SOLIDS:</b> 46%  <b>WEIGHT PER GALLON:</b> 10.6 lbs. /gal.  <b>PRACTICAL COVERAGE:</b> Covers approximately 350–450 sq. ft. per gallon (32–42 m<sup>2</sup> per 3.78 L). Less on rough or porous surfaces. Thin with up to 8 oz. water per gallon only if paint is too thick for sprayer.  <b>RECOMMENDED FILM THICKNESS:</b>                      4.0 mil Wet                      1.3 mil Dry</p>
FEATURES	
<ul style="list-style-type: none"> <li>Great hide &amp; coverage</li> <li>Excellent touch-up</li> <li>Excellent burnish resistance</li> <li>Washable film</li> <li>Sheen equivalent to MPI gloss level #2, defined as 'a velvet-like finish' and is comparable to competitor Low Sheen products</li> <li>Smooth, uniform finish</li> <li>Easy application spray, brush and roll</li> </ul>	
APPLICATION	SYSTEM RECOMMENDATIONS
<p>Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, polyester brush or airless sprayer. Surface conditions and application technique can also impact coverage.</p> <p><b>Airless Spray:</b>                      Pressure: 2000 PSI                      Tip: 0.015"–0.021"</p> <p><b>Brush:</b> premium-quality polyester brush  <b>Roller:</b> premium quality synthetic, 3/8" nap  <b>Dry Time @ 77 °F and 50% Relative Humidity</b>  <b>To The Touch:</b> 1 hour  <b>Recoat:</b> 4 hours  <b>Application Temperature:</b> 50–90 °F (10–32 °C)  <b>Washing:</b> Allow at least 7 days before washing. Use mild detergent and sponge.</p>	<p><b>Drywall/Wallboard (new):</b>                      1 Coat: Valspar® Primer                      1–2 Coats: Professional Interior Latex Eggshell Paint</p> <p><b>Plaster:</b>                      1 Coat: Valspar® Primer                      1–2 Coats: Professional Interior Latex Eggshell Paint</p> <p><b>New Wood/Composition Board:</b>                      1 Coat: Valspar® Int/Ext Bonding Primer                      1–2 Coats: Professional Interior Latex Eggshell Paint</p> <p><b>Interior Concrete Block:</b>                      1 Coat: Valspar® Block filler                      1–2 Coats: Professional Interior Latex Eggshell Paint</p> <p><b>Masonry:</b>                      1 Coat: Valspar® Masonry and Stucco Primer                      1–2 Coats: Professional Interior Latex Eggshell Paint</p> <p><b>Previously Painted Surfaces:</b>                      1–2 Coats: Professional Interior Latex Eggshell Paint</p> <p>Recommended one coat primer if the painting project requires a bold color transition. This will improve the topcoat hiding power.</p>

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

Revised  
8/8/2017

### SURFACE PREPARATION

**General:** Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove all wax, grease, dirt, chalk, mildew, loose and peeling paint and other foreign matter. Remove gloss from shiny surfaces. Repair all cracks and nail holes with patching compound. Painting over wallpaper is not recommended. New or bare surfaces should be primed with an appropriate Valspar® primer.

**Drywall and Plaster:** Fill cracks, pits and voids with patching compound. Allow new plaster to fully cure and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Primer.

**Wood:** Sand wood smooth. Patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Interior/Exterior Bonding Primer.

**Concrete Block:** Concrete block surfaces and mortar should be fully cured, usually 30 days. Remove all loose material or dust. Fill pores of bare concrete block with Valspar® Block filler, then top coat.

**Masonry:** New concrete, masonry surfaces and mortar should be cured, usually 30 days. Remove all form release or curing agents. Remove all loose material or dust. Prime bare surfaces with Valspar® Masonry and Stucco Primer, then top coat.

### LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulation.

### CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

### CAUTIONS CONT'D

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:**  
**1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631  
877.825.7727  
valsparpaint.com  
Version: 11800E