



### GENERAL DESCRIPTION

**Valspar Professional Interior Latex Semi-Gloss** is professional grade paint with great hide & coverage and excellent durability. It creates a washable film with excellent block resistance. The paint's excellent flow & levelling properties provide a smooth, uniform finish. Ideal for residential re-paint projects, remodeling and new home construction; this paint is formulated for spray, brush and roll application on properly prepared interior walls and ceilings.

### PRODUCT FEATURES

- Great hide & coverage
- Excellent block resistance
- Washable film
- Excellent flow and levelling
- Easy application spray, brush and roll

### RECOMMENDED USES

Properly prepared interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement and metal.

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material. Protect from freezing.

**Packaging:**

- Gallon – 4 per carton
- 5 gallon pail

### COMPOSITION

**Base and Fill Levels**

	(oz./gal.)
<b>High Hiding White</b>	128
<b>Light Base (11911)</b>	124
<b>Medium Base (11912)</b>	120
<b>Neutral Base (11914)</b>	116

### APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, polyester brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction. Note: Some deep or bright colors may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage.

**Airless Spray:**

- Pressure: 2000 PSI
- Tip: 0.015"–0.021"

**Brush:** Premium-quality polyester

**Roller:** Premium-quality roller 3/8" nap

### SYSTEM

#### RECOMMENDATIONS

**Drywall/Wallboard (new):**

- 1 Coat: Valspar® Primer
- 1–2 Coats: Professional Interior Latex Semi-Gloss Paint

**Plaster:**

- 1 Coat: Valspar® Primer
- 1–2 Coats: Professional Interior Latex Semi-Gloss Paint

**New Wood/Composition Board:**

- 1 Coat: Valspar® Int/Ext Bonding Primer
- 1–2 Coats: Professional Interior Latex Semi-Gloss Paint

**Interior Concrete Block:**

- 1 Coat: Valspar® Block filler
- 1–2 Coats: Professional Interior Latex Semi-Gloss Paint

**Masonry:**

- 1 Coat: Valspar® Masonry and Stucco Primer
- 1–2 Coats: Professional Interior Latex Semi-Gloss Paint

**Previously Painted Surfaces:**

- 1–2 Coats: Professional Interior Latex Semi-Gloss Paint

Recommended one coat primer if the painting project requires a bold color transition. This will improve the topcoat hiding power.

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic resin

**Pigment Type:** Titanium dioxide

**Viscosity:** 97–103 Krebs Units

**Sheen:** 35–45 Units @ 60° angle

**Flashpoint:** N/A

**VOC (g/L):** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406

**Volume Solids:** 27%

**Weight Solids:** 40%

**Weight Per Gallon:** 10.1 lbs./gal.

**Practical Coverage:** Covers up to 350–450 sq. ft. per gallon (32–42 m<sup>2</sup> per 3.78 L). Less on rough or porous surfaces. Thin with up to 8 oz. water per gallon only if paint is too thick for sprayer.

**Recommended Film Thickness:**

- 4.0 mil Wet
- 1.1 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To The Touch:** 1 hour

**Recoat:** 4 hours

**Washing:** Allow at least 7 days before washing. Use mild detergent and sponge.

**Application Temperature:** 50–90 °F (10–32 °C)

### CERTIFICATIONS

Current as of: 8/8/2017

MPI #54, GPS-1, GPS-2	Pending
MPI #147, GPS-1, GPS-2	Pending
UL Greenguard Gold	Yes
LEED (US)	Yes
LEED (Canada)	Yes

### REGULATORY COMPLIANCE

Current as of: 8/8/2017

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

### CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.



# Valspar® Professional Interior Latex Semi-Gloss Paint

---

## No. 11900 Series

### SURFACE PREPARATION

#### **General:**

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove all wax, grease, dirt, chalk, mildew, loose and peeling paint and other foreign matter. Remove gloss from shiny surfaces. Repair all cracks and nail holes with patching compound. Painting over wallpaper is not recommended. New or bare surfaces should be primed with an appropriate Valspar® primer.

#### **Drywall and Plaster:**

Fill cracks, pits and voids with patching compound. Allow new plaster to fully cure and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Primer.

#### **Wood:**

Sand wood smooth and patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Interior/Exterior Bonding Primer.

#### **Concrete Block:**

Concrete block surfaces and mortar should be fully cured, usually 30 days. Remove all loose material or dust. Fill pores of bare concrete block with Valspar® Block filler, then top coat.

#### **Masonry:**

New concrete, masonry surfaces and mortar should be cured, usually 30 days. Remove all form release or curing agents. Remove all loose material or dust. Prime bare surfaces with Valspar® Masonry and Stucco Primer, then top coat.

### LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### LIMITED WARRANTY

This product is warranted to meet the application, appearance and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions, and excludes failure due to deterioration of the underlying surface, structural defects, or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT, AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

### CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

#### **EMERGENCY MEDICAL TELEPHONE:**

**1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631

877.825.7727

valsparpaint.com

Revised: 8/8/17

Version: 11900E