



Valspar® Cabinet and Furniture Interior/Exterior Semi-Gloss Paint

GENERAL DESCRIPTION

Valspar® Cabinet and Furniture oil-enriched enamel provides a strong factory-like finish with no brush marks, exceptional durability and excellent stain resistance. It also protects against scuff marks, fading and scratches and prevents doors and drawers from sticking.

PRODUCT FEATURES

- Oil-enriched enamel
- Exceptional durability
- Strong factory-like finish with no brush marks.
- Prevents doors and drawers from sticking.
- Excellent stain resistance.
- Resists scuff marks, fading and scratches.

RECOMMENDED USES

Properly prepared or previously painted interior and exterior doors, trim and cabinets.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

Quart – 4 per carton

Gallon – 4 per carton

COMPOSITION

Base and Fill Levels (oz./gal.)

Ultra White (4881736, 4881737)	124
Tint Base C (4881738, 4881739)	116

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Previously Painted Surfaces: Thoroughly clean the surface and allow to dry. Remove all dirt, dust, chalk, rust, grease, wax and mildew. Scrape off loose and peeling paint. Dull glossy surfaces by sanding

Bare Wood, Plywood/Composition Board: For best results over heavily stained areas and bleeding woods such as redwood and cedar, use a coat of stain-blocking primer.

Metal: Remove rust on galvanized surfaces and prime with a rust-inhibitive metal primer. For drastic color changes or deep, vivid colors, prime with this product or an appropriate tintable primer for your optimal color accuracy and coverage.

Clean Mildew from the Surface: Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray. Thinning not required. Finish with light roller strokes in one direction. Certain deep or bright colors may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

Airless Spray:

Pressure: 2000 PSI

Tip: 0.013"–0.017"

Brush: Premium-quality

Roller: Premium-quality roller 3/8" nap

PRODUCT SPECIFICATIONS

Vehicle Type: 100% Acrylic

VOC (g/L): < 50 g/L as per 40 CFR 59.406

Flashpoint: 499°F

Viscosity: 103 - 109 Krebs Units

Volume Solids: 33 ± 2%

Weight Solids: 50 ± 4%

Weight Per Gallon: 10.8lb

Sheen: Semi-Gloss

Coverage: Up to 400 sq. ft./gallon

Recommended Film Thickness: 4 mils wet, 1.5 mils dry

Application Temperature: 50-90°F and 50%

Relative Humidity

Dry Time:

To Touch: 2 hours

Recoat: 4 hours

REGULATORY COMPLIANCE

Current as of: 4/5/2022

AIM VOC:

EPA National Rule

OTC

OTC II

SCAQMD

CARB 2000

CARB 2019

CARB 2020

Canada

CLEANUP/DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.



Valspar® Cabinet and Furniture Interior/Exterior Semi-Gloss Paint

LEAD WARNING

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

LIFETIME LIMITED WARRANTY

If this product, when applied according to product application instructions to a properly prepared interior surface, fails to perform to your complete satisfaction for as long as you own your home, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the product. This is your sole remedy under this warranty. This warranty is made to the original residential consumer paint purchaser and is not transferable. **THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. Valsparpaint.com / 1-877-VALSPAR.

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. DANGER:** Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. 12162 (311)

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.
EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732

Cleveland, OH
valsparpaint.com
888.313.5569
Revised: 4/25/2022
VALC&FSG