



### GENERAL DESCRIPTION

Valspar® Medallion® Plus Interior Paint & Primer is a 100% acrylic, high-hiding formula offering good scrubability with durable, fade-resistant color. Valspar® Medallion® Plus resists stains, scuffs & scrubs by providing an even, one-coat finish. Offering a lifetime limited warranty, this formula is also mold- and mildew-resistant, and is GREENGUARD Gold certified for indoor air quality.

#### Product Features:

- High-hiding
- Good scrubability
- One-coat coverage
- Great durability
- 100% acrylic
- Provides a mildew-resistant finish
- GREENGUARD Gold certified for low chemical emissions
- Easy cleanup

### WHERE TO USE

Properly prepared interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement, and metal.

### SHIPPING AND PACKAGING

#### Freight Classification:

Paint or paint related material. Protect from freezing.

#### Packaging:

Quart – 4 per carton  
Gallon – 4 per carton  
5 gallon pail

### COMPOSITION

#### Base and Fill Levels

	(oz./gal.)
Ultra White	126
Tint Base	124
Clear Base	116

### APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .015"-.019" tip). Thinning not required. Some deep or bright colors, surface conditions and application techniques may impact coverage and require multiple coats to achieve your optimal coverage. For additional application tips go to Valspar.com.

#### Airless Spray:

**Pressure:** 2000 PSI

**Tip:** 0.015–0.019"

**Brush:** Premium-quality polyester

**Roller:** Premium-quality roller 3/8" nap

### CLEANUP/STORAGE/ DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

### PRODUCT SPECIFICATIONS

- o **Vehicle Type:** Acrylic
- o **Viscosity:** 92–98 Krebs Units
- o **Gloss:** 10-20 Units @ 85° angle
- o **Flashpoint:** N/A
- o **VOC (g/L):** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406
- o **Volume Solids:** 43%
- o **Weight Solids:** 57%
- o **Weight Per Gallon:** 11.44 lbs./gal.
- o **Practical Coverage:** 400 sq. ft. per gallon (27-37 m<sup>2</sup> per 3.78 L) depending on surface porosity. Do not thin.
- o **Recommended Film Thickness:**  
4.0 mil Wet 2.0 mil Dry
- o **Dry Time @ 77 °F and 50% Relative Humidity**
  - ▯ **To The Touch:** 30–60 minutes
  - ▯ **Recoat:** 2–4 hours
- o **Application Temperature:** 50–90 °F (10–32 °C)



# Valspar® Medallion® Plus Interior Latex Eggshell Paint

---

## Series 2200

### **SURFACE PREPARATION**

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. Priming: This product can be used to prime patched areas, unpainted surfaces and lightly stained areas before applying it as the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, prime with this product or an appropriate tintable primer for your optimal color accuracy and coverage.

### **LIFETIME LIMITED WARRANTY**

LIFETIME LIMITED WARRANTY: If this product, when applied according to product application instructions, to a properly prepared exterior residential surface, peels or blisters, for as long as you own your residence, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product sufficient to repair the peeling or blistering free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the product. This is your sole remedy under this warranty. This warranty is made to the original residential consumer paint purchaser and is not transferable. THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which vary from state to state. Valsparpaint.com/1-877-VALSPAR..

### **LEAD WARNING**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **CAUTIONS**

**Tint, Clear Base:** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

**Ultra-White Base:** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

**EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732**

Valspar, Cleveland, Ohio 44115  
1-877-VALSPAR (825-7727)  
valsparpaint.com  
Revised: 9/21/22  
Version: 2200EG