

### GENERAL DESCRIPTION

Valspar® Door and Trim Oil Enriched Enamel features an anti-fade formula that is tintable to 1000+ colors, making customization easy. It is as durable as an oil-based paint but with the benefits of a water-based paint, including resisting yellowing and easy cleanup with just soap and water. This Valspar® product also resists scuffs and scratches and requires little to no prep work.

### PRODUCT FEATURES

- Anti-Fade Formula
- Resists scuffs and scratches
- Soap-and-water cleanup
- No sanding or priming needed
- Durable as oil
- Tintable to 1,000+ colours

### WHERE TO USE

Bare wood, previously painted wood or metal in sound condition or properly prepared laminate.

### SHIPPING AND PACKAGING

#### **Freight Classification:**

Paint or paint related material. Protect from freezing.

#### **Packaging:**

Quart – 4 per carton

### COMPOSITION

	<b>Base and Fill Levels</b> (ml/qt.)
<b>Ultra White</b> (0015357)	917
<b>Base 4</b> (0015359)	857

### APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform colour. Apply with a premium-quality roller or polyester brush. Note: Two thin coats are required. Bare wood or some deep or bright colours may require an additional coat to obtain complete hide. Surface conditions and application technique can also impact coverage. Allow to dry thoroughly before recoating or use.

**Airless Spray:** Pressure: 2000 PSI

**Tip:** 0.015–0.019"

**Brush:** premium-quality polyester

**Roller:** 3/6" – 3/8" premium-quality

DO NOT USE FOAM ROLLER

### SYSTEM

### RECOMMENDATIONS

#### **New Wood:**

2 Coats: Valspar® Door and Trim Oil Enriched Enamel

#### **Previously Paint Surfaces:**

2 Coats: Valspar® Door and Trim Oil Enriched Enamel

#### **Laminate:**

1 Coat: Valspar® Multi-Surface Primer

2 Coats: Valspar® Door and Trim Oil Enriched Enamel

For improved adhesion on extremely smooth surfaces use 1 coat of Valspar® Bonding Primer

Recommended one coat of primer if the painting project requires a bold transition. This will improve the topcoat hiding power.

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic-Alkyd Hybrid

**Viscosity:** 87–95 Krebs Units

**Gloss:** 50-60 @ 60° angle

**Flashpoint:** N/A

**VOC (g/L):** < 50 g/L □ 0.42 lb./gal as per 40 CFR 59.406

**Weight Per Gallon:** 5.0 kg

**Volume Solids:** 35%

**Weight Solids:** 51%

**Practical Coverage:** Covers approximately 37 m<sup>2</sup> per 3.78 L (400 sq. ft. per gallon) depending on surface porosity.

#### **Recommended Film Thickness:**

4.0 mil Wet                      1.4 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To Touch:** 4 hours

**Recoat:** 8-12 hours

**Washing Instructions:** Wait at least 7 days before washing with a mild detergent and soft sponge

**Application Temperature:** 10–32 °C (50–90 °F)

### REGULATORY COMPLIANCE

Current as of: 3/18/2020

SCAQMD                      Yes

CARB 2000 SCM            Yes

CARB 2007 SCM            Yes

OTC/LADCO                Yes

US National                Yes

### **SURFACE PREPARATION**

**Previously Painted Surfaces and Bare Wood:** Thoroughly clean the surface and allow to dry. Remove all dirt, dust, chalk, rust, grease, wax and mildew. Scrape off loose and peeling paint. Dull glossy surfaces by sanding.

**Laminate:** Apply a coat of bonding primer.

**Bare Metal:** Apply a rust-inhibitive metal primer.

### **LEAD WARNING**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting your local health authority.

### **LIFETIME LIMITED WARRANTY**

1. Warranty: If this product fails to perform to your satisfaction, return it to the store with your proof of purchase for your choice of either replacement of an equivalent quantity of product free of charge or for a refund of the original purchase price.

2. Exclusions: This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product. **EXCEPT IF YOU PURCHASED THE PRODUCT AS A CONSUMER RESIDING IN THE PROVINCE OF QUÉBEC, IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES AND CONDITIONS, INCLUDING WARRANTIES AND CONDITIONS OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY."**

### **MILDEW**

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

### **CLEANUP/STORAGE/ DISPOSAL**

Clean up with soap and water. Do not freeze. Keep container closed when not in use. Do not transfer to other containers for storage or disposal. In case of spillage, absorb with inert material. Dispose of container and/or unused contents in accordance with local, municipal, or provincial regulations.

### **CAUTIONS**

**DANGER OF COMBUSTION. MAY IRRITATE EYES.** Do not get in eyes. Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard. Dispose of in accordance with local fire regulations. Keep out of reach of children. **FIRST AID TREATMENT:** Contains: acrylic modified alkyd, surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

Valspar, Cleveland, Ohio 44115  
1-800-785-1276  
valspar.ca  
Revised: 5/9/23  
VALCDTSG  
Version: 2