



# Valspar® Pro-Hide® Exterior Oil Primer

---

## Series 91316

### GENERAL DESCRIPTION

Valspar® Pro-Hide® Exterior Oil Primer offers great stain and tanning blocking all while resisting peeling, blistering and cracking. Pro-Hide® Exterior Oil Primer assures a uniform topcoat to many exterior home surfaces, and can be applied by spray, brush or roller.

#### **Product Features:**

- Great stainblocking
- Blocks tannins
- Resists peeling, blistering & cracking
- Fast drying

### WHERE TO USE

Properly prepared exterior wood, hardboard, masonry and metal.

### SHIPPING AND PACKAGING

#### **Freight Classification:**

Paint or paint related material. Protect from freezing.

#### **Packaging:**

Gallon – 4 per carton

### COMPOSITION

#### **Base and Fill Levels**

(oz./gal.)

White

128

### APPLICATION

Stir primer thoroughly before and during use.

Apply with a premium-quality polyester brush, pad applicator, roller or airless sprayer. If applying by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface. Allow to dry 24 hours before applying a top coat.

#### **Airless Spray:**

**Pressure:** 2000 PSI

**Tip:** 0.017–0.021"

**Brush:** Premium-quality polyester

**Roller:** Premium-quality roller

### CLEANUP/STORAGE/

### DISPOSAL

Clean brushes and tools with a regionally compliant cleaner following manufacturer's safety instructions. Wash hands with soap and water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Alkyd

**Pigment Type:** Titanium dioxide

**Viscosity:** 85-95 Krebs Units

**Sheen:** 0–10 Units @ 85° angle

**Flashpoint:** N/A

**VOC:** < 350 g/L as per 40 CFR 59.406

**Volume Solids:** 55%

**Weight Solids:** 77%

**Weight Per Gallon:** 12.8 lbs./gal

**Practical Coverage:** Up to 400 sq. ft. per gallon (37 m<sup>2</sup> per 3.78 L) depending on surface porosity.

**Recommended Film Thickness:**

4.0 mil Wet, 2.2 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To Touch:** 2-4 hours

**Recoat:** 24 hours

**Application Temperature:** 50–90 °F (10–32 °C)

**Storage Temperature:** 40–90 °F (5–32 °C)



# Valspar® Pro-Hide® Exterior Oil Primer

---

## Series 91316

### **SURFACE PREPARATION**

Surface should be clean, dry and dull. Glossy surfaces should be dulled. Thoroughly clean the surface and remove all dirt, dust, chalk, rust, grease, wax, mildew, rust and peeling paint and allow to dry. See technical data page for additional surface prep.

### **LEAD WARNING**

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **LIMITED WARRANTY**

This product is warranted to meet the application, appearance, and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal or lesser value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state. CONTRACTOR AND COMMERCIAL CUSTOMERS: When used for commercial or nonresidential applications, this product is warranted to perform as indicated on the product label and to be free of material defects. At its option, Valspar will replace or refund the original purchase price of this product if it does not perform as labeled or is proven to be defective. All other warranty terms above apply. [Valsparpaint.com/1-877-VALSPAR](http://Valsparpaint.com/1-877-VALSPAR).

### **CAUTIONS**

DANGER!  
HARMFUL OR FATAL IF SWALLOWED.  
COMBUSTIBLE!  
VAPOR HARMFUL.  
IRRITATES EYES, SKIN AND RESPIRATORY TRACT.  
Before using, carefully read CAUTIONS on back panel.

Contents are COMBUSTIBLE. Keep away from heat and open flame. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

**EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732**

Valspar, Cleveland, Ohio 44115  
1-877-VALSPAR (825-7727)  
[valsparpaint.com](http://valsparpaint.com)  
Revised: 9/21/22  
Version: 91316