



Valspar® Pro-Hide® Multi-Purpose Int/Ext Primer

Series 91218

GENERAL DESCRIPTION

Valspar® Pro-Hide® Multi-Purpose Interior/Exterior Latex Primer & Sealer is a 100% acrylic formula that seals and blocks out most common household stains. High-hiding and great for drastic color changes, Pro-Hide® Multi-Purpose Primer & Sealer improves the finish of all topcoats and offers outstanding adhesion even to glossy surfaces. Pro-Hide® Multi-Purpose Primer & Sealer is fast drying and can be top-coated with either latex or oil paints.

Product Features:

- Primer & sealer
- Great stainblocking
- High-hiding
- Great adhesion
- Fast drying

WHERE TO USE

Use on properly prepared interior and exterior surfaces including drywall, masonry, wood, metal, PVC piping, and previously painted surfaces.

SHIPPING AND PACKAGING

Freight Classification:

Paint or paint related material. Protect from freezing.

Packaging:

Gallon – 4 per carton
5 gallon pail

COMPOSITION

Base and Fill Levels

(oz./gal.)

White 128

APPLICATION

Application: Stir paint thoroughly. Intermix containers to ensure uniform color. Apply when air, surface and product temperatures are above 50°F. No reduction necessary. If applying by spray, back-rolling is recommended for drywall, plaster, and masonry.

Airless Spray:

Pressure: 2000 PSI

Tip: 0.019–0.021"

Brush: Premium-quality polyester

Roller: Premium-quality roller 3/8" nap

CLEANUP/STORAGE/ DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

PRODUCT SPECIFICATIONS

- **Vehicle Type:** Vinyl Acetate Ethylene Copolymer
- **Viscosity:** 92-102 Krebs Units
- **Sheen:** 0–9 Units @ 85° angle
- **Flashpoint:** N/A
- **VOC:** < 50 g/L as per 40 CFR 59.406
- **Volume Solids:** 31%
- **Weight Solids:** 46%
- **Weight Per Gallon:** 10.7 lbs./gal
- **Practical Coverage:** up to 400 sq. ft. per gallon (37 m² per 3.78 L) depending on surface porosity.
- **Recommended Film Thickness:** 4.0 mil Wet 1.3 mil Dry
- **Dry Time @ 77 °F and 50% Relative Humidity**
 - o **To Touch:** 1 hour
 - o **Recoat:** 2 hours for latex, 4 hours for oil
- **Application Temperature:** 50–90 °F (10–32 °C)
- **Storage Temperature:** 40–90 °F (5–32 °C)



Valspar® Pro-Hide® Multi-Purpose Int/Ext Primer

Series 91218

SURFACE PREPARATION

Surface should be clean, dry and dull. Remove all contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand existing, peeling or cracking paint to a sound surface. Sand glossy surfaces. Drywall: Fill cracks and holes with spackling compound and sand smooth. Joint compounds must be cured and sanded smooth. Remove sanding dust. Masonry: Allow to cure at least 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow surface to dry 7 days and prime with Pro-Hide® Masonry and Stucco Primer. Plaster: Allow to cure at least 30 days. Treat textured, soft, porous or powdery plaster with a solution of 1-pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry. Wood, Hardboard, Paneling: Sand bare wood to a fresh surface. Patch holes and imperfections with a wood filler and sand smooth. Remove sanding dust. Steel: Remove rust and mill scale with sandpaper, steel wool or other abrading method. Prime bare steel the same day as cleaned. Aluminum & Galvanized Metal: Wash to remove any oil, grease or other surface contamination using a water-based cleaner-degreaser. Do not use hydrocarbon solvents for cleaning. Remove all corrosion with sandpaper, steel wool or other abrading method. PVC Piping: Lightly scuff sand the surface for best adhesion..

LEAD WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

This product is warranted to meet the application, appearance, and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal or lesser value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state. CONTRACTOR AND COMMERCIAL CUSTOMERS: When used for commercial or nonresidential applications, this product is warranted to perform as indicated on the product label and to be free of material defects. At its option, Valspar will replace or refund the original purchase price of this product if it does not perform as labeled or is proven to be defective. All other warranty terms above apply. Valsparpaint.com/1-877-VALSPAR.

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732

Valspar, Cleveland, Ohio 44115
1-877-VALSPAR (825-7727)
valsparpaint.com
Revised: 9/21/22
Version: 91218