



### GENERAL DESCRIPTION

Valspar® Skylight® Ceiling Paint is in an interior latex paint meant for properly prepared textured ceiling surfaces or previously painted and primed plaster, drywall, acoustical tile and wood. It offers excellent hide, stain blocking, and is mold- & mildew-resistant and offers a lifetime limited warranty. GREENGUARD Gold certified for indoor air quality, Valspar® Skylight® Ceiling Paint covers ceilings seamlessly, offering easy cleanup from a spatter-resistant formula.

#### Product Features:

- Excellent hide
- Spatter resistant
- GREENGUARD Gold certified for low chemical emissions
- Fast drying
- Easy cleanup

### SHIPPING AND PACKAGING

#### Freight Classification:

Paint or paint related material. Protect from freezing.

#### Packaging:

Gallon – 4 per carton  
5 Gallon

### COMPOSITION

#### Base and Fill Levels

(oz./gal.)

White

128

### APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 10-32 °C (50-90 °F). Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .381-.483 mm tip). Thinning not required. Certain deep or bright colours may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

#### Airless Spray:

**Pressure:** 2000 PSI

**Tip:** .381-.483 mm

**Brush:** Premium-quality

**Roller:** Premium-quality roller roller 3/8" nap

### CLEANUP/STORAGE/

### DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

### WHERE TO USE

Properly prepared and durable textured or plain interior ceilings, including previously painted and primed plaster, drywall and acoustical tile.

### PRODUCT SPECIFICATIONS

- **Vehicle Type:** Acrylic resin
- **Viscosity:** 97-105 Krebs Units
- **Sheen:** 0-5 units at 85°
- **Flashpoint:** N/A
- **VOC (g/L):** < 50 g/L 0.42 lb./gal as per 40 CFR 59.406
- **Weight Per Gallon:** 10.65 lbs.
- **Volume Solids:** 31%
- **Weight Solids:** 45%
- **Practical Coverage:** Covers approximately 400 sq. ft. per gallon (37 m2 per 3.78 L) depending on surface porosity. Significantly less on acoustical tile.
- **Recommended Film Thickness:**
- 40 mil Wet 1.2 mil Dry
- **Dry Time @ 77 °F and 50% Relative Humidity**
- **To Touch:** 1 hour
- **Recoat:** 2-4 hours
- **Application Temperature:** 50–90 °F (10–32 °C)
- **Storage Temperature:** 40–90 °F (5–32 °C)



# Valspar® Skylight® Ceiling Paint

## Series 1015

---

### **SURFACE PREPARATION**

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Patch cracks and spot prime. Remove gloss from shiny surfaces. Acoustical tile: Vacuum or dust tiles to remove embedded dust. To maintain the sound absorbing qualities of the tile, do not use a primer. Apply ceiling paint directly to the tiles. Test vinyl-coated tiles to ensure adhesion. Do not attempt to fill or clog acoustical perforations. "Blown-on" soft-fibred ceilings: Caution! All waterbased paints will loosen or deteriorate a "blown-on" soft-fibred ceiling surface and make for a difficult repair. If you are not sure about your ceiling texture type, apply a small test area in a closet or other hidden spot. If deterioration occurs and if painting is necessary, priming with an oil-based primer may help minimize the deterioration. Do not use a latex primer.

### **Clean Mildew from the Surface:**

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

### **LIFETIME LIMITED**

### **WARRANTY**

#### **LIFETIME LIMITED WARRANTY:**

1. Warranty: If this product fails to perform to your complete satisfaction for as long as you own the property, return it to the store with your proof-of-purchase for either replacement of an equivalent quantity of product free of charge or for a refund of the original purchase price.
2. Exclusions: This warranty shall not apply to any defect, damage or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product.

### **LEAD WARNING**

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **CAUTIONS**

MAY IRRITATE EYES. Do not get in eyes. Keep out of reach of children. FIRST AID TREATMENT: Contains: surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

Valspar, Mississauga,  
Ontario L4Z 1T5  
Canada  
1-800-785-1276  
[Valspar.ca](http://Valspar.ca)  
Revised: 4/05/24  
Version: 1015A