

GENERAL DESCRIPTION

Concrete & masonry Waterproofer with a siloxane formula that penetrates the surface to help keep water out. This clear finish will not alter the color or texture of the concrete or masonry surface. It protects against water, salt, dirt, chemicals and freeze / thaw cycles.

PRODUCT FEATURES

- Clear, waterproofing coating for properly prepared interior and exterior floors such as driveways, patios, walkways, pool decks, living spaces, basements and other surfaces
- Protects from sun, water, salt, dirt and chemical damage
- Protects against freeze / thaw cycles
- Maintains the beauty of concrete without changing its appearance

RECOMMENDED USES

Use on interior and exterior aggregate, concrete, masonry, mortar and flagstone. Do not use below grade.

COMPOSITION

Base and Fill Levels

Clear 128 (oz./gal.)

REGULATORY COMPLIANCE

Current as of: 1/1/2023

SCAQMD	Yes
CARB	Yes
OTC	Yes
LADCO	Yes
EPA	Yes
Colorado AIM	Yes

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room or physician immediately. **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

SURFACE PREPARATION

For use over bare concrete and masonry surfaces only. Newly poured concrete must be cured at least 30 days. Newly installed pavers should weather a minimum of 60 days; excess joint sand should be swept off the surface prior to application. All concrete must be clean, dry and free of grease, oil, paint, sealers, etc. A high-pressure water wash is recommended. To spot clean, use Valspar® Fast Prep® Ready-to-Use Solution, following label instructions. Surface should have the feel of 120-grit sandpaper at minimum and readily absorb water. **Test Surface Porosity Before Sealing:** Avoid using this product on nonporous, sealed surfaces. To test, place a few drops of water on the surface. If water immediately sinks in, the surface is porous enough to use this finish. If water remains on the surface, concrete must be etched with Valspar® Fast Prep® Ready-to-Use Solution, following label instructions. If the surface does not feel like 120-grit sandpaper following the first application, a second etching is required. Allow 24 hours to dry before waterproofing.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Use a roller or low-pressure, garden-type sprayer. While the first coat is still wet (typically between 5-10 minutes), apply a second coat to maximize protection. Allow 5-10 minutes for final penetration, then use a clean, dry cloth to wipe off all excess that did not soak into the surface. Do not pond or puddle this product.

CLEANUP STORAGE AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

PRODUCT SPECIFICATIONS

Vehicle Type: Siloxane
Viscosity: Water thin
VOC (g/L): less than 50 g/L
VolumeSolids: 7%
Weight Solids: 7%
Weight Per Gallon: 8.3
Practical Coverage: Covers approximately 100 - 200 sq. ft. per gallon depending on surface porosity.
Dry Time @ 77 °F and 50% Relative Humidity
To the Touch: 1 hour
Application Temperature: 50–90 °F (10–32 °C)

LIMITED WARRANTY

This warranty is made to you, the product purchaser who owns the property where the product is applied. This warranty is not transferable, except that if a contractor purchased and applied the product to the property, then the warranty is transferable to you. This warranty is only valid when the product is applied and maintained according to product application and maintenance instructions to a properly prepared surface. If the product fails to perform in accordance with applicable product literature, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect, damage or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application of the product. Your exclusive remedy and the sole liability of Valspar under this warranty, is the replacement of product or refund, and does not include labor or costs associated with the application or removal of any product. **IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.** Some states do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights and you may have other rights that vary from state to state.

Valspar, Cleveland, Ohio 44115
 Product Information Hotline: 877.825.7727
valspar.com
 Revised: 3.6.2023