



Valspar® Elastomeric Masonry, Stucco & Brick Flat Paint

No. 5332032 Series

GENERAL DESCRIPTION

Valspar® Elastomeric Masonry, Stucco & Brick Paint forms a weatherproof barrier against nature's harsh extremes using advanced Flex Right™ Technology for resistance to cracking and peeling.

Stucco and masonry structures expand and contract in response to the weather and structural stresses. Unlike typical exterior paints, this coating fills and bridges hairline cracks (up to 1/16"), helping to prevent damaging water penetration. It passes Federal Specification TT-C-555B, sec 3.3.3, withstanding 98 mph wind-driven rain.

This premium-quality coating protects your home like a flexible blanket, keeping your masonry, stucco, and brick safe and beautiful for years to come. It is available in an extra white or a deep base and can be tinted to a variety of colors!

PRODUCT FEATURES

- Flex Right™ Technology – Formulated to resist cracking and peeling
- Withstands 98 mph wind-driven rain
- Highly resistant to alkali - can be applied to surfaces with pH 6-13
- Thick, high-build coverage
- Bridges hairline cracks (up to 1/16")
- Flexes with hot and cold temperatures
- Excellent spray application
- Rain-Ready Technology®
Ready in just 1.5 hours — guards the freshly painted surface from runs, blisters or water marks once rain showers begin
- Fade resistant
- Gives a mold- & mildew-resistant finish

RECOMMENDED USES

Properly prepared exterior masonry surfaces including cement, cinder block, stucco, concrete and brick. Do not use on glazed brick, floors or steps.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

- Gallon – 4 per carton
- 5 gallon pail

APPLICATION

Paint only when air or surface temperatures are between 35–90 °F (2–32 °C). Use a paint paddle to stir paint up from the bottom of the can. Intermix containers of the same color. Apply this product heavily to achieve the best weatherproofing characteristics. No reduction necessary. Cover grass and shrubbery with plastic or cloth. Apply two coats of this product to ensure that the correct film thickness (6.5–8.4 mil dry film) is achieved. The recommended spreading rate on a smooth surface is 130 sq. ft. per gallon per coat. On rough stucco or other uneven surfaces, this may be as low as 90 sq. ft. per gallon per coat. NOTE: For the two coats, you will need one gallon for every 45–65 sq. ft.

Roller (Preferred):

Premium-quality 1/2" to 1–1/2" nap synthetic roller cover. Always roll with a fully loaded wet roller – never dry roll. Do not stretch this coating. Be sure all low spots and gaps are covered. It is normal for painted surfaces to show roller marks.

Airless Spray:

Apply using 2300 PSI with a 0.021" tip. Adjust pressures to suit your needs. Always follow spray application by back-rolling with a wet applicator. This will ensure that the paint is worked into the surface.

Brush (Not recommended):

Use only for small touch-ups.

SYSTEM RECOMMENDATIONS

Masonry and Stucco:

- Self-priming
- 2 Coats: Elastomeric Masonry and Stucco Paint

COMPOSITION Base and Fill Levels

	(oz./gal.)
Extra White (5332032, 5332033)	124
Deep Base (5331666, 5331667)	118

PRODUCT SPECIFICATIONS

- Vehicle Type:** Titanium Dioxide
- Pigment Type:** Proprietary Acrylic
- Viscosity:** 110–120 Krebs Units
- Gloss:** 0–10 Units @ 85° angle
- Flashpoint:** N/A
- VOC (g/L):** less than 50 g/L 0.42 lb/gal as per 40 CFR 59.406
- VOC (lbs./gal.):** 0.34
- Volume Solids:** 45%
- Weight Solids:** 61%
- Weight Per Gallon:** 11.46 lbs./gal.
- Practical Coverage:** Apply 2 coats of product to ensure best coverage and proper overall performance.
- Smooth surface:** Covers up to 130 sq. ft. per gallon (12 m2 per 3.78 L).
- Rough or uneven surfaces:** Covers up to 90 sq. ft. per gallon (8.3 m2 per 3.78 L).
- Recommended Film Thickness:**
14.5-18.5 mil Wet 6.5-8.4 mil Dry
- DryTime@77°F and 50% Relative Humidity To The Touch:** 2 hours
- Recoat:** 24 hours
- Full Cure:** 30 days
- Application Temperature:** 35–90 °F (2–32 °C)
- Elongation:** 312%; Method ASTM D412
- Tensile Strength:** 295 psi; Method ASTM D412

CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.



Valspar® Elastomeric Masonry, Stucco & Brick Flat Paint

No. 5332032 Series

SURFACE PREPARATION

General: Read the Lead Warning paragraph. Apply paint to clean, sound surfaces. Large cracks, crumbling areas or water damage may need professional repair. New concrete or stucco must cure at least 7 days before application. This product can be applied to a surface with a pH of 6-13.

Cleaning the surface: Old or existing surfaces; remove dirt, grease, mildew, algae, efflorescence and loose, peeling coating. A pressure washer and masonry and stucco cleaner will ensure a clean, chalk and dirt free surface. Follow all label and equipment instructions and rinse well. Caution: Improper pressure washer use may cause damage to stucco.

Filling in cracks and patching: Hairline cracks (1/16" or less) can be covered with this product. Cracks larger than 1/16" must be cleaned to remove all loose stucco or masonry. For stucco, fill gaps with exterior stucco-texture finish, following label instructions. For masonry gaps, fill with concrete patch. Note: Large areas of crumbling masonry indicate a serious problem, consult a professional contractor.

Priming: Priming is not required on masonry surfaces in sound or good condition (cured, no efflorescence, etc.).

Caulking: Caulk all joints, seams and cracks around windows, doors and trim to eliminate sources of moisture entry.

Facts about efflorescence: Efflorescence is a crusty white material that migrates to the surface of masonry over time. It is caused by water within the wall itself. Find and repair the source of water entry (cracked cap tiles, open joints or cracks) before painting. Remove it using a pressure washer, wire brush or scraper. Remove stubborn efflorescence with a mild, muriatic-acid solution. Protect skin and eyes by wearing rubber gloves and eye goggles.

Clean mildew from the surface: To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIFETIME LIMITED WARRANTY

This warranty is made to you, the product purchaser, who owns the property where the product is applied, and is not transferable. If this product, when applied and maintained according to product application and maintenance instructions to a properly prepared surface, peels or blisters for as long as you own the property, Valspar shall, upon presentation of proof-of-purchase, either replace an equivalent quantity of product sufficient to repair the peeling or blistering free of charge or refund the original purchase price. For a replacement or refund, please visit the store where the product was purchased. This warranty shall not apply to any defect, damage or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product. Your exclusive remedy and the sole liability of Valspar under this warranty, is the replacement of product or refund, and does not include labor or costs associated with the application or removal of any product. IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY. Some states do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state. Valsparpaint.com/1-877-VALSPAR.

CAUTIONS

Extra White, Deep Base:

CONTAINS ZINC. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

101 W. Superior Ave, Cleveland, OH 44115
888.313.5569
valsparpaint.com
Revised: 5/11/23
VALMSBELAST
Version: 1