

GENERAL DESCRIPTION

Valspar® Restoration® is an ideal primer and sealer for both interior and exterior restoration and disaster recovery. Drying in just 30 minutes, Valspar® Restoration® seals out water and smoke stains as well as related odors – providing a mold- and mildew-resistant finish. Additional benefits include excellent adhesion as well as high hiding.

PRODUCT FEATURES

- Seals out water and smoke stains and related odors
- Excellent adhesion
- Provides a mold- and mildew resistant finish
- High hiding
- Dries in 30 minutes – recoat in 1 hour
- Ideal for restoration and disaster recovery
- GREENGUARD Gold Certified

RECOMMENDED USES

Properly prepared interior and exterior drywall, wood, plaster, masonry, and metal surfaces.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

Quart – 4 per carton
Gallon – 4 per carton
5 Gallon pail

COMPOSITION

Base and Fill Levels

	(oz./gal.)
White	128

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

General: Surfaces must be clean, dry and dull prior to application. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. All dust should be removed.

Drywall: Fill cracks and holes with joint compound and sand smooth.

Plaster: Must be dry, fully cured and in good condition. Remove all chalky residue.

Wood: Sand to a fresh surface. Patch imperfections with wood filler. Heavily stained areas, including tannin stains on wood, may require an appropriate stain-blocking primer.

Masonry: All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface.

Metal: New galvanized surfaces should be allowed to age 6 months before painting. Wash to remove any oil, grease or other surface contamination using a water-based cleaner-degreaser. Do not use hydrocarbon solvents for cleaning. Remove all corrosion with sandpaper, steel wool or other abrading method.

For smoke and heavily stained areas: Thoroughly clean the surface before applying.

Clean Mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

APPLICATION

Stir primer thoroughly before and during use. Apply with a premium-quality polyester brush, roller or airless sprayer. If applying by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface. First coat of primer locks in the stain and odor. Apply at temperatures above 35° F. Prior to painting, check to be sure the air, surface and material temperatures are above 35° F and at least 5° F above the dew point. Avoid using if rain or snow is expected within 2-3 hours. Air and surface temperatures must not drop below 35° F for 48 hours after application.

Airless Spray:

Pressure: 2000 PSI
Tip: 0.015–0.021"

Brush: Premium-quality polyester

Roller: Premium-quality roller 3/8" nap

PRODUCT SPECIFICATIONS

Vehicle Type: Styrene Acrylic

VOC (g/L): < 100 g/L as per 40 CFR 59.406

Flashpoint: N/A

Viscosity: 105 – 111 Krebs Units

Volume Solids: 38 ± 2%

Weight Solids: 50 ± 2%

Weight Per Gallon: 9.99lbs

Finish: 12-20 units @ 85°

Coverage: Up to 400 sq. ft./gallon

Recommended Film Thickness:

4 mils Wet

1.5 mils Dry

Dry Time: @ 77 °F and 50% Relative Humidity

To The Touch: 30 minutes

Recoat: 1 hour

Application Temperature: Above 40°F

Tintable up to 2oz of Novo II black.

CLEANUP/DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.



Valspar® Restoration® Interior-Exterior Latex Primer-Sealer

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. 15 (1/10)

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.
**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

Cleveland, OH
valsparpaint.com
888.313.5569
Revised: 7/18/2023
VALRESERVEES

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.