



GENERAL DESCRIPTION

Valspar® Medallion® Plus Interior Paint & Primer is a 100% acrylic, high-hiding formula offering good scrubability with durable, fade-resistant color. Valspar® Medallion® Plus resists stains, scuffs & scrubs by providing an even, one-coat finish. Offering a satisfaction guarantee lifetime limited warranty, this formula is also mold- and mildew-resistant, and is GREENGUARD Gold certified for indoor air quality.

Product Features:

- High-hiding
- Good scrubability
- One-coat coverage
- Great durability
- 100% acrylic
- Provides a mildew-resistant finish
- GREENGUARD Gold certified for low chemical emissions
- Easy cleanup

WHERE TO USE

Properly prepared interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement, and metal.

SHIPPING AND PACKAGING

Freight Classification:

Paint or paint related material. Protect from freezing.

Packaging:

- Quart – 4 per carton
- Gallon – 4 per carton
- 5 gallon pail

COMPOSITION

Base and Fill Levels

	(oz./gal.)
Ultra White	126
Tint Base	124
Clear Base	116

APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .381-.483 mm tip). Thinning not required. Some deep or bright colors, surface conditions and application techniques may impact coverage and require multiple coats to achieve your optimal coverage. For additional application tips go to Valspar.ca

Airless Spray:

Pressure: 2000 PSI

Tip: .381-.483 mm

Brush: Premium-quality polyester

Roller: Premium-quality synthetic roller 3/8" nap

CLEANUP/STORAGE/ DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

PRODUCT SPECIFICATIONS

- o **Vehicle Type:** Acrylic
- o **Viscosity:** 92–98 Krebs Units
- o **Gloss:** 10-20 Units @ 85° angle
- o **Flashpoint:** N/A
- o **VOC (g/L):** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406
- o **Volume Solids:** 43%
- o **Weight Solids:** 57%
- o **Weight Per Gallon:** 11.44 lbs./gal.
- o **Practical Coverage:** 400 sq. ft. per gallon (27-37 m² per 3.78 L) depending on surface porosity. Do not thin.
- o **Recommended Film Thickness:** 4.0 mil Wet 2.0 mil Dry
- o **Dry Time @ 77 °F and 50% Relative Humidity**
 - ▯ **To The Touch:** 30–60 minutes
 - ▯ **Recoat:** 2–4 hours
- o **Application Temperature:** 50–90 °F (10–32 °C)



Valspar® Medallion® Plus Interior Latex Eggshell Paint

Series 1022

SURFACE PREPARATION

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. Priming: This product can be used to prime patched areas, unpainted surfaces and lightly stained areas before applying it as the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, prime with this product or an appropriate tintable primer for your optimal color accuracy and coverage.

Clean Mildew from the Surface:

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

SATISFACTION GUARANTEE **LIFETIME LIMITED** **WARRANTY:**

SATISFACTION GUARANTEE LIFETIME LIMITED WARRANTY:

1.Warranty: If this product fails to perform to your complete satisfaction for as long as you own the property, return it to the store with your proof of purchase for either replacement of an equivalent quantity of product free of charge or for a refund of the original purchase price.

2.Exclusions: This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product.

CAUTIONS

MAY IRRITATE EYES. Do not get in eyes. Keep out of reach of children. FIRST AID TREATMENT: Contains: surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes

Valspar, Mississauga,
Ontario L4Z 1T5
Canada
1-800-785-1276
Valspar.ca
Revised: 4/2/24
Version: 1022A