



GENERAL DESCRIPTION

Valspar® Pro-Hide® Silver 5000 Interior latex paint offers dependable performance ideal for residential and commercial new and repaint projects. Even application by spray, brush or roller, Pro-Hide® Silver 5000 also offers easy cleanup with soap & water. Pro-Hide® Silver 5000 offers a limited warranty and is GREENGUARD Gold certified for indoor air quality.

Product Features:

- Good hide & coverage
- Even application
- GREENGUARD Gold certified for low chemical emissions
- Easy cleanup

WHERE TO USE

Properly prepared interior walls, trim and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.

SHIPPING AND PACKAGING

Freight Classification:

Paint or paint related material. Protect from freezing.

Packaging:

Gallon – 4 per carton
5 gallon

COMPOSITION

Base and Fill Levels (oz./gal.)

White	128
Pastel	124
Clear Base	116

APPLICATION

Stir paint thoroughly. Internix containers for uniformity. Apply product when surface, air and product temperatures are between 10-32 °C. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .381-.483 mm tip). Thinning not required. Paint the ceiling first, then walls and trim. For roller application, cover approximately a 2' x 2' (60 x 60 cm) area using an "N" pattern. Finish with light roller strokes in one direction. Some deep or bright colours, surface conditions and application techniques may impact coverage and require multiple coats to achieve your optimal coverage. For additional application tips go to Valspar.ca.

Airless Spray:

Pressure: 2000 PSI

Tip: .381-.483 mm

Brush: Premium-quality brush

Roller: Premium-quality synthetic roller 3/8" nap

PRODUCT SPECIFICATIONS

- o **Vehicle Type:** Vinyl Acrylic
- o **Viscosity:** 90–100 Krebs Units
- o **Gloss:** 10 – 20 Units @ 85°
- o **Flashpoint:** N/A
- o **VOC (g/L):** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406
- o **Volume Solids:** 30%
- o **Weight Solids:** 42%
- o **Weight Per Gallon:** 10.2 lbs./gal.
- o **Practical Coverage:** 400 sq. ft. per gallon (37 m² per 3.78 L) depending on surface porosity. Do not thin
- o **Recommended Film Thickness:** 4.0 mil Wet
1.2 mil Dry
- o **Dry Time @ 77 °F and 50% Relative Humidity**
 - ▯ **To The Touch:** 1 hour
 - ▯ **Recoat:** 4 hours
- o **Application Temperature:** 50–90 °F (10–32 °C)
- o **Storage Temperature:** 40–90 °F (5–32 °C)

CLEANUP/STORAGE/

DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.



Valspar® Pro-Hide Silver® 5000 Interior Eggshell Latex Paint

Series 1072

SURFACE PREPARATION

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. Priming: This product can be used to prime patched areas, unpainted surfaces and lightly stained areas before applying it as the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, prime with this product or an appropriate tintable primer for your optimal color accuracy and coverage.

Clean Mildew from the Surface

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

LEAD WARNING

If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY:

LIMITED WARRANTY:

- 1.Warranty: If this product fails to perform in accordance with applicable product literature, return it to the store with your proof-of-purchase for either replacement of an equivalent quantity of product free of charge or for a refund of the original purchase price.
- 2.Exclusions: This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product.

CAUTIONS

MAY IRRITATE EYES. Do not get in eyes. Keep out of reach of children. FIRST AID TREATMENT: Contains: surfactants. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes.

Valspar, Mississauga,
Ontario L4Z 1T5
Canada
1-800-785-1276
Valspar.ca
Revised: 4/08/24
Version: 1072A